



Interested in learning more about security?

SANS Institute InfoSec Reading Room

This paper is from the SANS Institute Reading Room site. Reposting is not permitted without express written permission.

Securing Solaris

When configuring a Solaris system for production, a balance must exist between system manageability and security. It is necessary to determine the role the system will play in order to determine what services it needs to run. The objective is to keep things simple. By dedicating separate machines for different tasks, it is expected that only one or two services will run on a host. This methodology makes it easier to isolate applications, harden, and troubleshoot. This type of minimalist approach runs only what is absol...

Copyright SANS Institute
Author Retains Full Rights

AD

A banner for Watchfire. On the left, there is a blurred image of a login form with fields for "login : YZEIF 1 1" and "password :". To the right of this image is a dark blue rectangular box containing the text "Others can assess Web applications for vulnerabilities." in white. On the far right is the Watchfire logo, which consists of a red flame icon followed by the word "watchfire" in a lowercase, sans-serif font.

Securing Solaris

Angela Orebaugh

October 2, 2000

When configuring a Solaris system for production, a balance must exist between system manageability and security. It is necessary to determine the role the system will play in order to determine what services it needs to run. The objective is to keep things simple. By dedicating separate machines for different tasks, it is expected that only one or two services will run on a host. This methodology makes it easier to isolate applications, harden, and troubleshoot. This type of minimalist approach runs only what is absolutely necessary. Keeping a Solaris system secure is a daily task. This includes keeping up on exploits, patches, and reviewing log files. The following suggestions are just the beginning to securing your Solaris system. There are some additional steps that may need to be taken depending on the systems role in the organization, and some of the steps listed may not apply. Consulting the listed references for additional information is highly recommended.

1. Install the Operating System

Securing a Solaris system starts with the installation. This consists of an "initial" install of the latest version of the Solaris operating system. With every new release, Sun incorporates improvements and additional features to enhance system security. Be sure that the system is disconnected from the network, or connected to an isolated network while performing the install and the subsequent hardening tasks. Attaching the system to a public network before it is secured can lead to a possible compromise. To get the necessary patches, use a second machine to download the files and burn them to CD-ROM, or connect to the isolated network to transfer them.

Choosing the minimum "core" install increases security by reducing the amount of software and possible exploits. The core installation also decreases the amount of disk space needed for the install. Additional necessary packages can be added at a later time.

The system will need to be partitioned to allocate disk space for system files, logging and applications. The four recommended partitions are /, /usr, /var and /opt. The /usr and /opt partitions are used for application installation. The size of these partitions varies according to available disk space and the size of the applications being installed. The /var partition is used for system logging and protects the root (/) partition from overfilling. The /swap partition is created automatically from the initial install.

2. Apply Patches

Once the initial installation is complete and the system has rebooted, it is time to install the patches. Recommended Patch Clusters can be downloaded from Sun at <http://www.sunsolve.sun.com>. Maintenance Updates (MU) are also available to service contract customers. They should be applied before the Recommended Patch Clusters. If a patch fails with a "return code 8", then the patch applies to a package not installed on the system. A "return code 2" indicates that the patches have already been applied.

3. Secure the inetd

The next step to securing Solaris is the removing unnecessary services from the inetd.conf file. This can be done by placing a pound sign (#) in front of the line that is not needed. It is ideal to comment out everything in the inetd.conf file and add them back as needed. Telnet and FTP will be replaced with SSH. Ideally, comment out ftp, tftp, systat, rexd, ypupdated, netstat, rstatd, rusersd, sprayd, walld, exec, talk, comsat, rquotad, name, uucp, sadmind, login, finger, chargen, echo, time, daytime, discard, telnet, imap, pop3, dtspc, fs, kcms, and all rpc services.

4. Secure the startup scripts

The startup scripts reside in /etc/rc2.d and /etc/rc3.d. Many of the services here are not needed and pose potential security vulnerabilities. To stop a script from starting, replace the capital S with a lowercase s (or K with a lowercase k). Some example services that should be disabled are:

Automounter /etc/rc2.d/S74autofs

Sendmail /etc/rc2.d/S88sendmail and /etc/rc1.d/K57sendmail

RPC /etc/rc2.d/S71rpc

SNMP /etc/rc2.d/S76snmpdx

NFS server /etc/rc3.d/S15nfs.server

5. Enable logging

The default Solaris system logging occurs in */var/adm*. Enable additional logging by creating two additional logging files, */var/adm/sulog* and */var/adm/loginlog*. The *sulog* will log successful and unsuccessful *su* attempts. The *loginlog* will catch consecutive failed login attempts. Enable the files by:

```
#touch /var/adm/sulog

#touch /var/adm/loginlog

#chmod 600 /var/adm/sulog

#chmod 600 /var/adm/loginlog

#chown root /var/adm/sulog

#chown root /var/adm/loginlog

#chgrp sys /var/adm/sulog

#chgrp sys /var/adm/loginlog
```

Uncomment the following line in */etc/syslog.conf* to log authentication messages:

```
#auth.notice ifdef(`LOGHOST', /var/log/authlog, @loghost)
```

Then perform the following to create the proper *authlog* file:

```
#touch /var/log/authlog

#chmod 600 /var/log/authlog

#chown root /var/log/authlog
```

6. Miscellaneous security tasks

Set the TCP initial sequence number generation parameters to protect against hijacking and spoofing.

In the file */etc/default/inetinit* set `TCP_STRONG_ISS=2`

Protect against buffer overflow attacks by adding the following to */etc/system*:

```
Set noexec_user_stack=1

Set noexec_user_stack_log=1
```

Ensure that root can only access the console by making sure the following line in */etc/default/login* is not commented out:

```
CONSOLE=/dev/console
```

Remove, lock or comment out unnecessary accounts, including "sys", "uucp", "nuucp", "smtp" and "listen". The best way to disable them is to put "*"LK*" in the password field of the */etc/shadow* file. The following command line options can also be used to remove or lock accounts:

```
Remove – #passmgmt –d account
```

```
Lock – #passwd –l account
```

Change the /etc/motd to contain warnings about inappropriate and unauthorized use of the system.

Remove sendmail packages – SUNWsndmr and SUNWsndmu

Remove group write permission of the /etc directory by performing the following:

```
chmod -R g-w /etc
```

Disable routing by performing the following:

```
#touch /etc/notrouter
```

Remove /etc/hosts.equiv, /.rhosts

Disable the Stop-A abort sequence by changing the following in /etc/default/kbd:

```
KEYBOARD_ABORT=disabled
```

Enable EEPROM security:

```
#eeprom security-mode=full
```

New password: password

Retype new password: password

Do not make this password the same as root. Setting the security level to full requires a password to boot the system. "Command", instead of "full", may be used to provide protection without the need of a boot password.

7. Installing SSH

SSH is used for secure communications to the Solaris system. It encrypts all communications to the system. SSH has its own logging and access control, like TCP Wrapper, but is more secure since traffic cannot be sniffed. SSH can be obtained from <http://www.ssh.com> or <http://openssh.com>.

8. YASSP

Another resource to consider using is YASSP – Yet Another Secure Solaris Package. It automates some of the changes above and incorporates additional functionality such as Tripwire, TCP Wrappers, and a version of SSH. It can be found at <http://yassp.parc.xeorn.com>. It is recommended to install YASSP, then perform steps 3 through 7 as a safety check.

Boran, Sean. "Hardening Solaris: Securely Installing a Firewall Bastion Host." 25 October 1999. <http://securityportal.com/cover/coverstory19991025.html> (25 Sept. 2000)

Carnegie Mellon University. "Installing and Securing Solaris 2.6 Servers." 14 June 2000. <http://www.cert.org/security-improvement/implementations/i027.02.html> (24 Sept. 2000)

Galvin, Peter. "The Solaris Security FAQ." 7 July 2000. <http://www.sunworld.com/common/security-faq.html> (23 Sept. 2000)

Noordergraaf, Alex and Watson, Keith. "Solaris™ Operating Environment Minimization for Security: A Simple, Reproducible and Secure Application Installation Methodology." December 1999. <http://www.sun.com/blueprints/1299/minimization.pdf> (23 Sept. 2000)

Noordergraaf, Alex and Watson, Keith. "Solaris™ Operating Environment Network Settings for Security." December 1999. <http://www.sun.com/blueprints/1299/network.pdf> (23 Sept. 2000)

Noordergraaf, Alex and Watson, Keith. "Solaris™ Operating Environment Security." January 2000.
<http://www.sun.com/blueprints/0100/security.pdf> (23 Sept. 2000)

Spitzner, Lance. "Armoring Solaris." 27 August 2000. <http://www.enteract.com/~lspitz/armoring.html> (24 Sept. 2000)



Upcoming SANS Training

[Click Here for a full list of all Upcoming SANS Events by Location](#)

| | | | |
|---|-------------------------------|------------------------------------|-------------------|
| SANS London 2009 | London, United Kingdom | Nov 28, 2009 - Dec 06, 2009 | Live Event |
| SANS WhatWorks in Incident Detection Summit 2009 | Washington, DC | Dec 09, 2009 - Dec 10, 2009 | Live Event |
| SANS CDI East 2009 | Washington, DC | Dec 11, 2009 - Dec 18, 2009 | Live Event |
| SANS WhatWorks in Data Leakage Prevention and Encryption Summit 2010 | New Orleans, LA | Jan 07, 2010 - Jan 12, 2010 | Live Event |
| SANS Security East 2010 | New Orleans, LA | Jan 10, 2010 - Jan 18, 2010 | Live Event |
| SANS AppSec 2010 and WhatWorks in AppSec Summit | San Francisco, CA | Jan 29, 2010 - Feb 05, 2010 | Live Event |
| SANS Phoenix 2010 | Phoenix, AZ | Feb 14, 2010 - Feb 20, 2010 | Live Event |
| SANS Tokyo 2010 Spring | Tokyo, Japan | Feb 15, 2010 - Feb 20, 2010 | Live Event |
| SANS Geneva CISSP at HEG 2009 Autumn | OnlineSwitzerland | Nov 23, 2009 - Nov 28, 2009 | Live Event |
| SANS OnDemand | Books & MP3s Only | Anytime | Self Paced |