



Interested in learning more  
about network auditing?

# SANS Institute Security Consensus Operational Readiness Evaluation

This checklist is from the SCORE Checklist Project. Reposting is not permitted without express, written permission.

## Firewall Checklist

## Firewall Checklist

Prepared by: Krishni Naidu

### References:

Top Ten Blocking Recommendations Using Cisco ACL's Securing the Perimeter with Cisco IOS 12 Routers, Scott Winters, August 2000  
GIAC Firewall Practical: Implementation of Firewall Filters, Rick Thompson, August 2000  
Application Layer Firewalls vs Network Layer Firewalls: Which is the better choice, Keith D. Maxon, August 2000  
Top Ten Blocking Recommendations using Ipchains, Paul Tiedemann, August 2000  
What is Egress filtering and how can I implement it? Egress Filtering v0.2, Chris Brenton, February 2000  
IP Fragmentation attacks on Checkpoint firewalls, James Farrell, April 2001  
A comparison of packet filtering vs application level firewall technology, Ernest Romanofski, March 2001  
Designing a DMZ, Scott Young, March 2001  
The new firewall design question, Jamie R. Blerke, March 2001  
Securing your network perimeter by filtering inbound traffic on ACK and Reset bits on Nortel Routers, Oleg Krillov, February 2001  
Linux comes of age with stateful firewalling, Greg Hill, February 2001  
The desktop modem threat, Joe Livingston, July 2000  
DNS Security, Jeff Holland, July 2000  
The packet filter: A basic network security tool, Dan Strom, September 2000  
Perimeter filtering in a University setting, Elizabeth Mackenzie, September 2000  
Protecting your corporate laptops from Hackers, while they are on the road, Darrell Keller, May 2001  
Protecting yourself with Norton personal firewall, Mark Greco, May 2001  
The Distributed firewall, Daniel Wan, May 2001  
A brief taxonomy of firewalls – great walls of fire, Gary Smith, May 2001  
Check point firewall-1's stateful inspection, Michael J. Nikitas, April 2001  
Stealth firewalls, Brandon Gilespie, April 2001  
Firewall network appliance, Craig Simmons, October 2000

### Introduction

This checklist should be used to audit a firewall. This checklist does not provide vendor specific security considerations but rather attempts to provide a generic listing of security considerations to be used when auditing a firewall.

Only technical aspects of security are addressed in this checklist. Manual elements like physical protection for the firewall server is not considered.

Prior to using this checklist the following elements should be considered:

- Operating system: This checklist only defines the security items relating the firewall software and not to any security elements of the operating system.
- Port restrictions: A listing of ports to be restricted are highlighted in this checklist. However, prior to recommending that the ports be restricted, the auditor should ensure that the service associated with that port is not used by the business e.g. remote access via telnet. Where such situations exist this checklist attempts to provide alternate security options if the service is needed e.g. use SSH instead of Telnet.
- Modems within the internal network: Modems within the internal network are the biggest threat to subvert a firewall and thus the auditor should ensure that there

are no modems within the internal network. It is senseless performing an audit on the firewall when an even bigger threat exists via the modem. The auditor should perform war dialling to identify any modems within the internal network with tools like phonesweeper.

- Application level firewalls: The inherent nature of application level firewalls require that the operating system be as secure as possible due to the close binding of these two components. Thus, the auditor should ensure that the security on the operating system is secure before evaluating the security offered by the application level firewall.
- Defence in depth: It must be recognised that the firewall implementation is not an end to itself to provide security. Thus, it is vital that the auditor evaluate the security of the other components like IDS, operating systems, web applications, IIS/Apache, routers and databases. Some organisations have opted for firewall network appliances, which are firewalls loaded onto operating systems which have their security already preconfigured. In such instances, the auditor need only review the security of the firewall configuration instead of the operating system as well.
- Rulesets: This checklist provides a listing of best practice rulesets to be applied. However, the organisational requirements may not need all of the rulesets. For e.g. where an organisation has a need to allow access via the internet to critical servers, the rulesets would not include a deny rule to that internal IP address for the critical server. Instead it may provide for allow access to HTTP 80 to the critical IP and deny all other traffic to the critical IP. It must be noted that some elements of the recommended rulesets have to be applied irrespective of business requirements e.g. blocking private addresses (RFC1918), illegal addresses, standard unroutables, reserved addresses, etc.
- Laptop users: Most organisations use mobile laptops for telecommuting and on the road sales, etc. This provides a further vulnerability even if the organisation operates a VPN. The hacker could easily gain access to the laptop when it is connected to the internet and download tools to the laptop that can become a problem when the laptop is again connected to the corporate network. In a VPN situation, the hacker with access to the remote station once the tunnel is connected, can access the corporate network. In such a circumstance, it is important for the auditor to determine if laptop usage occurs and to evaluate whether personal firewalls are installed on these laptops prior to usage. This checklist provides a generic set of considerations for personal firewalls, but it does not provide any product specific security recommendations.

### Checklist

No.	Security Elements
1.	<p>Review the rulesets to ensure that they follow the order as follows:</p> <ul style="list-style-type: none"> <li>• anti-spoofing filters (blocked private addresses, internal addresses appearing from the outside)</li> <li>• User permit rules (e.g. allow HTTP to public webserver)</li> <li>• Management permit rules (e.g. SNMP traps to network management server)</li> <li>• Noise drops (e.g. discard OSPF and HSRP chatter)</li> <li>• Deny and Alert (alert systems administrator about traffic that is suspicious)</li> <li>• Deny and log (log remaining traffic for analysis)</li> </ul> <p>Firewalls operate on a first match basis, thus the above structure is important to ensure that suspicious traffic is kept out instead of inadvertently allowing them in by not following the proper order.</p>

2.	<p><b>Application based firewall</b></p> <p>Ensure that the administrators monitor any attempts to violate the security policy using the audit logs generated by the application level firewall.</p> <p>Alternatively some application level firewalls provide the functionality to log to intrusion detection systems. In such a circumstance ensure that the correct host, which is hosting the IDS, is defined in the application level firewall.</p> <p>Ensure that there is a process to update the application level firewall's vulnerabilities checked to the most current vulnerabilities.</p> <p>Ensure that there is a process to update the software with the latest attack signatures.</p> <p>In the event of the signatures being downloaded from the vendors' site, ensure that it is a trusted site.</p> <p>In the event of the signature being e-mailed to the systems administrator, ensure that digital signatures are used to verify the vendor and that the information transmitted has not been modified en-route.</p> <p>The following commands should be blocked for SMTP at the application level firewall:</p> <ul style="list-style-type: none"> <li>• EXPN (expand)</li> <li>• VRFY (verify)</li> <li>• DEBUG</li> <li>• WIZARD</li> </ul> <p>The following command should be blocked for FTP:</p> <ul style="list-style-type: none"> <li>• PUT</li> </ul> <p>Review the denied URL's and ensure that they are appropriate for e.g. any URL's to hacker sites should be blocked. In some instances organisations may want to block access to x-rated sites or other harmful sites. As such they would subscribe to sites, which maintain listings of such harmful sites. Ensure that the URL's to deny are updated as released by the sites that warn of harmful sites.</p> <p>Ensure that only authorised users are authenticated by the application level firewall.</p>
3.	<p><b>Stateful inspection</b></p> <p>Review the state tables to ensure that appropriate rules are set up in terms of source and destination IP's, source and destination ports and timeouts.</p> <p>Ensure that the timeouts are appropriate so as not to give the hacker too much time to launch a successful attack.</p> <p>For URL's</p> <ul style="list-style-type: none"> <li>• If a URL filtering server is used, ensure that it is appropriately defined in the firewall software. If the filtering server is external to the organisation ensure that it is a trusted source.</li> <li>• If the URL is from a file, ensure that there is adequate protection for this file to ensure no unauthorised modifications.</li> </ul> <p>Ensure that specific traffic containing scripts; ActiveX and java are stripped prior to being allowed into the internal network.</p> <p>If filtering on MAC addresses is allowed, review the filters to ensure that it is restricted to the appropriate MAC's as defined in the security policy.</p>
4.	<p><b>Logging</b></p> <p>Ensure that logging is enabled and that the logs are reviewed to identify any potential patterns that could indicate an attack.</p>
5.	<p><b>Patches and updates</b></p> <p>Ensure that the latest patches and updates relating to your firewall product is tested and installed.</p> <p>If patches and updates are automatically downloaded from the vendors' websites, ensure that the update is received from a trusted site.</p>

	<p>In the event that patches and updates are e-mailed to the systems administrator ensure that digital signatures are used to verify the vendor and ensure that the information has not been modified en-route.</p>																																				
6.	<p><b>Location – DMZ</b>          Ensure that there are two firewalls – one to connect the web server to the internet and the other to connect the web server to the internal network.          In the event of two firewalls ensure that it is of different types and that dual NIC's are used. This would increase security since a hacker would need to have knowledge of the strengths, weaknesses and bugs of both firewalls.          The rulesets for both firewalls would vary based on their location e.g. between web server and the internet and between web server and the internal network.</p>																																				
7.	<p><b>Vulnerability assessments/ Testing</b>          Ascertain if there is a procedure to test for open ports using nmap and whether unnecessary ports are closed.          Ensure that there is a procedure to test the rulesets when established or changed so as not to create a denial of service on the organisation or allow any weaknesses to continue undetected.</p>																																				
8.	<p><b>Compliance with security policy</b>          Ensure that the ruleset complies with the organisation security policy.</p>																																				
9.	<p>Ensure that the following spoofed, private (RFC 1918) and illegal addresses are blocked:</p> <ul style="list-style-type: none"> <li>Standard unroutables           <ul style="list-style-type: none"> <li>• 255.255.255.255</li> <li>• 127.0.0.0</li> </ul> </li> <li>Private (RFC 1918) addresses           <ul style="list-style-type: none"> <li>• 10.0.0.0 – 10.255.255.255</li> <li>• 172.16.0.0 – 172.31.255.255</li> <li>• 192.168.0.0 - 192.168.255.255</li> </ul> </li> <li>Reserved addresses           <ul style="list-style-type: none"> <li>• 240.0.0.0</li> </ul> </li> <li>Illegal addresses           <ul style="list-style-type: none"> <li>• 0.0.0.0</li> </ul> </li> <li>UDP echo</li> <li>ICMP broadcast (RFC 2644)</li> </ul> <p>Ensure that traffic from the above addresses is not transmitted by the interface.</p>																																				
10.	<p>Ensure that loose source routing and strict source routing (lsrsr &amp; ssrr) are blocked and logged by the firewall.</p>																																				
11.	<p><b>Port restrictions</b>          The following ports should be blocked:</p> <table border="1"> <thead> <tr> <th>Service</th> <th>Port Type</th> <th>Port Number</th> </tr> </thead> <tbody> <tr> <td>DNS Zone Transfers</td> <td>TCP</td> <td>53</td> </tr> <tr> <td>TFTP Daemon</td> <td>UDP</td> <td>69</td> </tr> <tr> <td>Link</td> <td>TCP</td> <td>87</td> </tr> <tr> <td>SUN RPC</td> <td>TCP &amp; UDP</td> <td>111</td> </tr> <tr> <td>BSD UNIX</td> <td>TCP</td> <td>512 – 514</td> </tr> <tr> <td>LPD</td> <td>TCP</td> <td>515</td> </tr> <tr> <td>UUCPD</td> <td>TCP</td> <td>540</td> </tr> <tr> <td>Open Windows</td> <td>TCP &amp; UDP</td> <td>2000</td> </tr> <tr> <td>NFS</td> <td>TCP &amp; UDP</td> <td>2049</td> </tr> <tr> <td>X Windows</td> <td>TCP &amp; UDP</td> <td>6000 – 6255</td> </tr> <tr> <td>Small services</td> <td>TCP &amp; UDP</td> <td>20 and below</td> </tr> </tbody> </table>	Service	Port Type	Port Number	DNS Zone Transfers	TCP	53	TFTP Daemon	UDP	69	Link	TCP	87	SUN RPC	TCP & UDP	111	BSD UNIX	TCP	512 – 514	LPD	TCP	515	UUCPD	TCP	540	Open Windows	TCP & UDP	2000	NFS	TCP & UDP	2049	X Windows	TCP & UDP	6000 – 6255	Small services	TCP & UDP	20 and below
Service	Port Type	Port Number																																			
DNS Zone Transfers	TCP	53																																			
TFTP Daemon	UDP	69																																			
Link	TCP	87																																			
SUN RPC	TCP & UDP	111																																			
BSD UNIX	TCP	512 – 514																																			
LPD	TCP	515																																			
UUCPD	TCP	540																																			
Open Windows	TCP & UDP	2000																																			
NFS	TCP & UDP	2049																																			
X Windows	TCP & UDP	6000 – 6255																																			
Small services	TCP & UDP	20 and below																																			

	Small services	TCP & UDP	20 and below	
	FTP	TCP	21	
	SSH	TCP	22	
	Telnet	TCP	23	
	SMTP (except external mail relays)	TCP	25	
	NTP	TCP & UDP	37	
	Finger	TCP	79	
	HTTP (except to external web servers)	TCP	80	
	POP	TCP	109 &110	
	NNTP	TCP	119	
	NTP	TCP	123	
	NetBIOS in Windows NT	TCP &UDP	135	
	NetBIOS in Windows NT	UDP	137 & 138	
	NetBIOS	TCP	139	
	IMAP	TCP	143	
	SNMP	TCP	161 &162	
	SNMP	UDP	161 &162	
	BGP	TCP	179	
	LDAP	TCP &UDP	389	
	SSL (except to external web servers)	TCP	443	
	NetBIOS in Win2k	TCP &UDP	445	
	Syslog	UDP	514	
	SOCKS	TCP	1080	
	Cisco AUX port	TCP	2001	
	Cisco AUX port (stream)	TCP	4001	
	Lockd (Linux DoS Vulnerability)	TCP &UDP	4045	
	Cisco AUX port (binary)	TCP	6001	
	Common high order HTTP ports	TCP	8000, 8080, 8888	
12.	Remote access If remote access is to be used, ensure that the SSH protocol (port 22) is used instead of Telnet.			
13.	File Transfers If FTP is a requirement, ensure that the server, which supports FTP, is placed in a different subnet than the internal protected network.			
14.	Mail Traffic Ascertain which protocol is used for mail and ensure that there is a rule to block incoming mail traffic except to internal mail.			
15.	ICMP (ICMP 8, 11, 3) Ensure that there is a rule blocking ICMP echo requests and replies. Ensure that there is a rule blocking outgoing time exceeded and unreachable messages.			
16.	IP Readdressing/IP Masquerading Ensure that the firewall rules have the readdressing option enabled such that internal IP addresses are not displayed to the external untrusted networks.			

17.	<p><b>Zone Transfers</b>  If the firewall is stateful, ensure packet filtering for UDP/TCP 53. IP packets for UDP 53 from the Internet are limited to authorised replies from the internal network. If the packet were not replying to a request from the internal DNS server, the firewall would deny it. The firewall is also denying IP packets for TCP 53 on the internal DNS server, besides those from authorised external secondary DNS servers, to prevent unauthorised zone transfers.</p>
18.	<p><b>Egress Filtering</b>  Ensure that there is a rule specifying that only traffic originating from IP's within the internal network be allowed. Traffic with IP's other than from the Internal network are to be dropped.  Ensure that any traffic originating from IP's other than from the internal network are logged.</p>
19.	<p><b>Critical servers</b>  Ensure that there is a deny rule for traffic destined to critical internal addresses from external sources. This rule is based on the organisational requirements, since some organisations may allow traffic via a web application to be routed via a DMZ.</p>
20.	<p><b>Personal firewalls</b>  Ensure that laptop users are given appropriate training regarding the threats, types of elements blocked by the firewall and guidelines for operation of the personal firewall. This element is essential, since often times personal firewalls rely on user prompt to respond to attacks e.g. whether to accept/deny a request from a specific address.  Review the security settings of the personal firewall to ensure that it restricts access to specific ports, protects against known attacks, and that there is adequate logging and user alerts in the event of an intrusion.  Ensure that there is a procedure to update the software for any new attacks that become known.  Alternatively most tools provide the option of transferring automatic updates via the internet. In such instances ensure that updates are received from trusted sites.</p>
21.	<p><b>Distributed firewalls</b>  Ensure that the security policy is consistently distributed to all hosts especially when there are changes to the policy.  Ensure that there are adequate controls to ensure the integrity of the policy during transfer, e.g. IPSec to encrypt the policy when in transfer.  Ensure that there are adequate controls to authenticate the appropriate host. Again IPSec can be used for authentication with cryptographic certificates.</p>
22.	<p><b>Stealth Firewalls</b>  Ensure that default users and passwords are reset.  Ensure that the firewall is appropriately configured to know which hosts are on which interface.  Review the firewall access control lists to ensure that the appropriate traffic is routed to the appropriate segments.  A stealth firewall does not have a presence on the network it is protecting and it makes it more difficult for the hacker to determine which firewall product is being used and their versions and to ascertain the topology of the network.</p>
23.	<p>Ensure that ACK bit monitoring is established to ensure that a remote system cannot initiate a TCP connection, but can only respond to packets sent to it.</p>
24.	<p><b>Continued availability of Firewalls</b>  Ensure that there is a hot standby for the primary firewall.</p>



# Upcoming SANS Training

[Click Here for a full list of all Upcoming SANS Events by Location](#)

SANS Secure Caribbean 2026	Kingston, JM	Feb 16, 2026 - Feb 21, 2026	Live Event
SANS Surge 2026	La Jolla, CAUS	Feb 23, 2026 - Feb 28, 2026	Live Event
SANS Dublin February 2026	Dublin, IE	Feb 23, 2026 - Feb 28, 2026	Live Event
SANS Secure Japan 2026	Tokyo, JP	Mar 02, 2026 - Mar 14, 2026	Live Event
SANS London March 2026	London, GB	Mar 02, 2026 - Mar 07, 2026	Live Event
SANS DC Metro March 2026	Arlington, VAUS	Mar 02, 2026 - Mar 07, 2026	Live Event
SANS Secure Singapore 2026	Singapore, SG	Mar 02, 2026 - Mar 14, 2026	Live Event
SANS Paris March 2026	Paris, FR	Mar 09, 2026 - Mar 14, 2026	Live Event
SANS Open-Source Intelligence Summit 2026	Arlington, VAUS	Mar 16, 2026 - Mar 22, 2026	Live Event
SANS Thailand March 2026	Bangkok, TH	Mar 16, 2026 - Mar 21, 2026	Live Event
SANS Amsterdam March 2026	Amsterdam, NL	Mar 16, 2026 - Mar 21, 2026	Live Event
SANS Melbourne March 2026	Melbourne, VIC, AU	Mar 16, 2026 - Mar 21, 2026	Live Event
SANS Cybersecurity Leadership Summit & Training 2026	Arlington, VAUS	Mar 17, 2026 - Mar 22, 2026	Live Event
SANS 2026	Orlando, FLUS	Mar 29, 2026 - Apr 03, 2026	Live Event
SANS London April 2026	London, GB	Apr 13, 2026 - Apr 18, 2026	Live Event
SANS Rome April 2026	Rome, IT	Apr 13, 2026 - Apr 18, 2026	Live Event
SANS Secure Australia 2026	Canberra, ACT, AU	Apr 13, 2026 - Apr 18, 2026	Live Event
SANS Rocky Mountain 2026	Denver, COUS	Apr 20, 2026 - Apr 25, 2026	Live Event
SANS SEC535 at AI Cybersecurity Summit & Training 2026	Arlington, VAUS	Apr 20, 2026 - Apr 27, 2026	Live Event
SANS AI Cybersecurity Summit & Training 2026	Arlington, VAUS	Apr 20, 2026 - Apr 27, 2026	Live Event
SANS Amsterdam April 2026	Amsterdam, NL	Apr 20, 2026 - Apr 25, 2026	Live Event
SANS ICS Munich 2026	Munich, DE	Apr 20, 2026 - Apr 25, 2026	Live Event
SANS Doha April 2026	Doha, QA	Apr 26, 2026 - Apr 30, 2026	Live Event
SANS Cyber Incident Management 2026	OnlineAU	Feb 09, 2026 - Feb 13, 2026	Live Event
SANS OnDemand	Books & MP3s OnlyUS	Anytime	Self Paced