



Interested in learning more about cyber security training?

## SANS Institute InfoSec Reading Room

This paper is from the SANS Institute Reading Room site. Reposting is not permitted without express written permission.

### Port Scanning Techniques and the Defense Against Them

Port Scanning is one of the most popular techniques attackers use to discover services that they can exploit to break into systems. All systems that are connected to a LAN or the Internet via a modem run services that listen to well-known and not so well-known ports. By port scanning, the attacker can find the following information about the targeted systems: what services are running, what users own those services, whether anonymous logins are supported, and whether certain network services require authentication. Por...

Copyright SANS Institute  
Author Retains Full Rights

AD

Veriato

Unmatched visibility into the computer activity of employees and contractors



Try Now

## **Port Scanning Techniques and the Defense Against Them**

Roger Christopher

October 5, 2001

### **Introduction**

Port Scanning is one of the most popular techniques attackers use to discover services that they can exploit to break into systems. All systems that are connected to a LAN or the Internet via a modem run services that listen to well-known and not so well-known ports. By port scanning, the attacker can find the following information about the targeted systems: what services are running, what users own those services, whether anonymous logins are supported, and whether certain network services require authentication. Port scanning is accomplished by sending a message to each port, one at a time. The kind of response received indicates whether the port is used and can be probed for further weaknesses. Port scanners are important to network security technicians because they can reveal possible security vulnerabilities on the targeted system.

Just as port scans can be ran against your systems, port scans can be detected and the amount of information about open services can be limited utilizing the proper tools. Every publicly available system has ports that are open and available for use. The object is to limit the exposure of open ports to authorized users and to deny access to the closed ports.

### **Port Scan Techniques**

To defend against port scans, you have to understand how port scans are performed. There are various port scanning techniques available. Port scans have been made automated by popular port scanning tools such as Nmap and Nessus.

The following scans are available for standard for Nmap and Nessus.

1. Address Resolution Protocol (ARP) scans discover active devices on the local network segment by sending a series of ARP broadcasts and incrementing the value for the target IP address field in each broadcast packet. This type of scan will have every IP device

on the network respond with its own IP address in response. This scan will effectively map out an entire network.

2. The Vanilla TCP connect scan is the most basic scanning technique. The scan uses the connect system call of an operating system on a target system to open a connection to every port that is open. The scan is extremely noisy and easily detectable. The targeted system logs will show connection requests and error messages for the services that accepted the connections.

3. The TCP SYN (Half Open) scans are called half open because the attacking system doesn't close the open connections. The attacking scanner will send a SYN packet to the target and wait for a response. If the port is open, the target will send a SYN|ACK. If the port is closed, the target will send an RST. This type of scan is difficult to detect. The target system is in charge of closing the open connections and the target, most likely, will not have the proper logging set up to detect this type of scan.

4. The TCP FIN scan has the ability to pass undetected through most firewalls, packet filters, and scan detection programs. The attacking system sends FIN packets to the targeted system. The closed ports will respond with an RST. The open ports will ignore the packets. The attacking system will take note of which ports it received an RST on and report on the ports that did not respond with an RST.

5. The TCP Reverse Ident scan discovers the username of the owner of any TCP connected process on the targeted system. This type of scan allows the attacking system to connect to open ports and use the ident protocol to discover who owns the process.

6. The TCP XMAS scan is used to identify listening ports on the targeted system. The scan manipulates the URG, PSH and FIN flags of the TCP header. If the port is closed on the targeted system, the target will send an RST. If the port is open, the port will ignore the packets.

7. The TCP NULL scan uses a series of uniquely configured TCP packets that contain a sequence number but no flags. If the target's TCP port is closed, the port will send an RST. If the port is open, the port will ignore the packet.

8. The TCP ACK scan is used to identify active web sites that may not respond to standard ICMP pings. The scan utilizes TCP packets with the ACK flag set to a probable port number. If the port is open, the target will send an RST in reply. If the port is closed, the target will ignore the packet.

9. The FTP Bounce Attack uses the ftp protocol support for proxy ftp connections. The beauty of this scan is that the attacker can hide behind an ftp server and scan another target without being detected. The downside is that most ftp servers have this service disabled.

10. The UDP ICMP port scan uses the UDP protocol. This port scan is successful in finding high number ports, especially in Solaris systems. The scan is slow and unreliable.

11. The ICMP ping-sweeping scan utilizes the ping command to do a sweep to see what systems are active. The downside is that most networks have the ICMP protocol either filtered or disabled.

(Fyodor)

### **Defending Against Port Scans**

If you have a publicly accessible server, the system will be vulnerable to port scans. There is no certain way to defeat port scans. The court systems have determined that performing port scans is not illegal. Port scans are illegal only if the attacker uses information from a port scan to exploit a vulnerability or open port on the system. So the question is: How do we limit the information our systems will give out?

One way to limit the information gained from port scans is to close unnecessary services on the targeted systems, i.e. if you are running a web server, http should be the only service offered. On UNIX systems, the easiest way to limit the information given to port scanners is to edit the /etc/inetd.conf and remark out any unnecessary services. You will also want to edit the /etc/init.d and the runlevel file that your system is utilizing. Remove any unneeded services. Also, ensure that your system is not running in the X11 mode. If you are running in the X11 mode, your system will broadcast the 6000 service whether you are logged in or not.

Another way to limit the information given to port scanners is to employ TCP Wrappers, where applicable. TCP Wrappers give the administrator the flexibility to permit or deny access to the services based upon IP addresses or domain names. TCP Wrappers work in conjunction with the /etc/inetd.conf file. TCP Wrappers works by invoking the tcpd daemon prior to providing the specified service. When an incoming request is detected coming in from an authorized port, TCP Wrappers will first check the /etc/hosts.allow file to see if the IP address or domain name has permissions to access the service. If no entry is found, TCP Wrappers will check the /etc/hosts.deny file. If no entry is found there, or if the statement ALL : ALL is found, TCP Wrappers will ignore the request and not permit the requested service to be utilized. When the system is port scanned, TCP Wrappers will still allow the service to be advertised, however, the scanner will not receive any additional information from the port unless the scan is coming from a host or domain specified in the /etc/hosts.allow file. When scanned, the system will list the service as being open. When the attacker tries to exploit the open port, TCP Wrappers will reject the incoming connection if it is not originated from an approved host or domain. The drawback of TCP Wrappers is that not all services are covered. Services such as http and smtp are not covered, and if improperly configured, will be susceptible to exploit. TCP Wrappers is not susceptible to IP spoofing. When an incoming request is detected, TCP Wrappers will perform a reverse DNS lookup on the requesting IP address. If the reverse lookup matches the requesting IP, TCP Wrappers will permit the connection. If the reverse lookup fails, TCP Wrappers will assume that

it is dealing with an unauthorized host and will not permit the connection.

Finally, another way to limit the amount of information given to port scans is to utilize PortSentry offered by Psionic. PortSentry detects connection requests on a number of selected ports. PortSentry is customizable and can be configured to ignore a certain number of attempts. The administrator can select what ports PortSentry will listen to for connection requests and the amount of invalid requests. The administrator will list ports that their system is not supporting. Upon detection, PortSentry will employ TCP Wrappers and make an entry into the `/etc/hosts.deny` file for the suspected intruder. PortSentry will also setup a default route statement for the offending system. The default route statement will route all packets from the offending system to either another system or a dead system. The result is that the targeted system will appear as being non-existent. On Linux systems, PortSentry is able to detect all TCP and UDP scans, whereas on Solaris systems are only able to detect the TCP Vanilla and UDP scans.

## **Conclusion**

Every system is vulnerable to port scanning. The best offense is a good defense. Never accept the default installation of operating systems. Most default installations have numerous ports open to allow a greater flexibility. Before a system is placed online, a port scan should be performed against the system. If more ports are open than required, close those ports. The greater number of services that your system offers, the more vulnerable the system. Periodically check the `/etc/inetd.conf`, the `/etc/init.d` file and the run control files on your system for unneeded services. If a system has been compromised, attackers may try to open up more ports on the system so they can more easily exploit the ports weaknesses. The more vigilant the system administrator is, the more resistant their system will be to penetration and the least likely they will be exploited.

## References

1. Anonymous. Maximum Security, Second Edition. Indianapolis: SAMS, 1998. 177 - 180.
2. McClure, Stuart; Scambray, Joel; Kurtz, George. Hacking Exposed, Network Security Secrets & Solutions. Berekley: Osborne/McGraw Hill, 1999. 38 - 51.
3. Fyodor. "The Art of Port Scanning." September 01, 1997. URL: [http://www.insecure.org/nmap/nmap\\_doc.html](http://www.insecure.org/nmap/nmap_doc.html). (September 25, 2001).
4. Psionic Software, Inc. URL: <http://www.psionic.com/abacus/portsentry>. (September 25, 2001).
5. Venema, Wietse. "TCP Wrappers 7.6 BLURB." March 21, 1997. URL: [ftp://ftp.porcupine.org/pub/security/tcp\\_wrappers\\_7.6.BLURB](ftp://ftp.porcupine.org/pub/security/tcp_wrappers_7.6.BLURB). (September 25, 2001).

© SANS Institute 2002, Author retains full rights.



# Upcoming SANS Training

[Click here to view a list of all SANS Courses](#)

SANS Sonoma 2019	Santa Rosa, CAUS	Jan 14, 2019 - Jan 19, 2019	Live Event
SANS Threat Hunting London 2019	London, GB	Jan 14, 2019 - Jan 19, 2019	Live Event
SANS Amsterdam January 2019	Amsterdam, NL	Jan 14, 2019 - Jan 19, 2019	Live Event
SANS Miami 2019	Miami, FLUS	Jan 21, 2019 - Jan 26, 2019	Live Event
Cyber Threat Intelligence Summit & Training 2019	Arlington, VAUS	Jan 21, 2019 - Jan 28, 2019	Live Event
SANS Dubai January 2019	Dubai, AE	Jan 26, 2019 - Jan 31, 2019	Live Event
SANS Las Vegas 2019	Las Vegas, NVUS	Jan 28, 2019 - Feb 02, 2019	Live Event
SANS Security East 2019	New Orleans, LAUS	Feb 02, 2019 - Feb 09, 2019	Live Event
SANS SEC504 Stuttgart 2019 (In English)	Stuttgart, DE	Feb 04, 2019 - Feb 09, 2019	Live Event
SANS Anaheim 2019	Anaheim, CAUS	Feb 11, 2019 - Feb 16, 2019	Live Event
SANS Northern VA Spring- Tysons 2019	Vienna, VAUS	Feb 11, 2019 - Feb 16, 2019	Live Event
SANS London February 2019	London, GB	Feb 11, 2019 - Feb 16, 2019	Live Event
SANS Zurich February 2019	Zurich, CH	Feb 18, 2019 - Feb 23, 2019	Live Event
SANS Secure Japan 2019	Tokyo, JP	Feb 18, 2019 - Mar 02, 2019	Live Event
SANS Scottsdale 2019	Scottsdale, AZUS	Feb 18, 2019 - Feb 23, 2019	Live Event
SANS New York Metro Winter 2019	Jersey City, NJUS	Feb 18, 2019 - Feb 23, 2019	Live Event
SANS Dallas 2019	Dallas, TXUS	Feb 18, 2019 - Feb 23, 2019	Live Event
SANS Riyadh February 2019	Riyadh, SA	Feb 23, 2019 - Feb 28, 2019	Live Event
SANS Reno Tahoe 2019	Reno, NVUS	Feb 25, 2019 - Mar 02, 2019	Live Event
Open-Source Intelligence Summit & Training 2019	Alexandria, VAUS	Feb 25, 2019 - Mar 03, 2019	Live Event
SANS Brussels February 2019	Brussels, BE	Feb 25, 2019 - Mar 02, 2019	Live Event
SANS Baltimore Spring 2019	Baltimore, MDUS	Mar 02, 2019 - Mar 09, 2019	Live Event
SANS Training at RSA Conference 2019	San Francisco, CAUS	Mar 03, 2019 - Mar 04, 2019	Live Event
SANS Secure India 2019	Bangalore, IN	Mar 04, 2019 - Mar 09, 2019	Live Event
SANS London March 2019	London, GB	Mar 11, 2019 - Mar 16, 2019	Live Event
SANS St. Louis 2019	St. Louis, MOUS	Mar 11, 2019 - Mar 16, 2019	Live Event
SANS Secure Singapore 2019	Singapore, SG	Mar 11, 2019 - Mar 23, 2019	Live Event
SANS San Francisco Spring 2019	San Francisco, CAUS	Mar 11, 2019 - Mar 16, 2019	Live Event
ICS Security Summit & Training 2019	Orlando, FLUS	Mar 18, 2019 - Mar 25, 2019	Live Event
SANS Secure Canberra 2019	Canberra, AU	Mar 18, 2019 - Mar 23, 2019	Live Event
SANS Norfolk 2019	Norfolk, VAUS	Mar 18, 2019 - Mar 23, 2019	Live Event
SANS Munich March 2019	Munich, DE	Mar 18, 2019 - Mar 23, 2019	Live Event
SANS Bangalore January 2019	OnlineIN	Jan 07, 2019 - Jan 19, 2019	Live Event
SANS OnDemand	Books & MP3s OnlyUS	Anytime	Self Paced