



Interested in learning  
more about security?

# SANS Institute InfoSec Reading Room

This paper is from the SANS Institute Reading Room site. Reposting is not permitted without express written permission.

## Deploying a website built using Oracle9iAS Portal

This paper is a case study of the deployment of a website built using the Portal component of Oracle9i Application Server (Oracle9iAS) in 2001. It has been submitted as the practical assignment for GSEC certification (Version 1.4b, Option 2). The paper describes the scenario and the product, Oracle9i AS (Standard Edition) Release 1 for Windows NT 4.0, before performing a high-level risk analysis of the website. The architecture implemented is discussed in terms of risk. The paper also identifies the security vulnerabil...

Copyright SANS Institute  
Author Retains Full Rights

AD



EMM Strategy on the right track?  
Know your security risks.

TAKE THE ASSESSMENT

# “Deploying a website built using Oracle9iAS Portal”

GIAC Security Essentials Certification – Version 1.4b Option 2

Steve Coates

## Abstract

This paper is a case study of the deployment of a website built using the Portal component of Oracle9i Application Server (Oracle9iAS) in 2001. It has been submitted as the practical assignment for GSEC certification (Version 1.4b, Option 2).

The paper describes the scenario and the product, Oracle9i AS (Standard Edition) Release 1 for Windows NT 4.0, before performing a high-level risk analysis of the website. The architecture implemented is discussed in terms of risk. The paper also identifies the security vulnerabilities discovered with Oracle9i AS during the six-month development period and the steps taken to harden an ‘out-of-the-box’ version.

Since the case study concerns a production system, certain details have been omitted or sanitised.

<b>Abstract</b> .....	<b>1</b>
<b>1. Before Snapshot</b> .....	<b>2</b>
1.1 Background.....	2
1.2 Description of Oracle9iAS Portal.....	2
1.3 Business benefits of using Oracle9iAS Portal.....	2
1.4 Editions of Oracle9iAS.....	3
1.5 Product Versions.....	4
1.6 High-Level Risk Analysis.....	5
<b>2. During Snapshot</b> .....	<b>7</b>
2.1 Business Issues.....	7
2.2 Risks.....	7
2.3 Vulnerability assessment.....	11
<b>3. After Snapshot</b> .....	<b>12</b>
3.1 Live Website.....	12
3.2 Additional Complications.....	12
3.3 Lessons Learned During Development.....	13
3.4 Reflection on SANS Material.....	14
<b>References</b> .....	<b>15</b>
<b>Appendix 1: Relevant Vulnerabilities (October 2000 - May 2001)</b> .....	<b>16</b>
<b>Appendix 2: Oracle9iAS Portal 3.0.7 Configuration Checklist</b> .....	<b>22</b>

## **1. Before Snapshot**

### **1.1 Background**

At the end of 2000, my company decided to bring its hosted website in-house. To do this it formed a new department, E-Commerce, sitting between Sales & Marketing (as the major providers of content) and Computer Services (who would take over running of the operational website). As one of the staff recruited from the Computer Services Department, my role was to lead former colleagues in the Technical Development Team to the implementation of a suitable web infrastructure.

Following a successful trial, we chose Oracle9i AS Portal as the key tool for us to build and content manage the new website. Since the Computer Services Department had certain preferred manufacturers and resellers, many other building blocks of the website were already identifiable; e.g., operating system (Windows NT 4.0), server hardware (Compaq), firewall software (Check Point), database software (Oracle), network provider, etc.

### **1.2 Description of Oracle9iAS Portal**

“Oracle9i Application Server” (Oracle9iAS) <sup>1</sup> is an application server supporting both Java 2 Enterprise Edition (J2EE) and PL/SQL, of which one major component is “Oracle9iAS Portal”.

Oracle9iAS Portal is intended as a common, integrated starting point for accessing data stored in an Oracle database (including files, images and applications) for both intranets and public websites. The majority of development is done via its wizard-based system, but it includes Java and PL/SQL development kits for more complex work. It comes with its own built-in caching.

### **1.3 Business benefits of using Oracle9iAS Portal**

Although (as WebDB) the product had started out as a way of leveraging database content to provide a simple intranet, it encouraged us to be one of the first companies to use it to host our own dynamic website.

Oracle9iAS Portal offered benefits to all areas of the business. For example, it meant that the Sales & Marketing Director could divide up the website and give different content responsibilities to different managers on different teams. Those content managers, without additional tools or knowledge of HTML, could use wizards to deploy simple applications in response to changing requests from the business. Hundreds of items (such as forms, reports, charts and lists of values) could simply be picked, configured and used. Additionally, support for over 20 languages plus

Portal Single Sign-On (SSO) with groups and permissions promised a website with one-to-one personalisation for our customers.

It offered the Computer Services Department a scaleable deployment architecture, starting from just a single Windows NT server and with portability to other operating systems. It also meant software support from a single vendor.

The E-Commerce department gained a database-driven website with ease of management and control for the overall environment and with support for Java, XML, PL/SQL and Perl.

### **1.4 Editions of Oracle9iAS**

The product was available for download from the Oracle web site in versions for Windows NT/2000, Linux (Intel) and Solaris (SPARC). The two main editions were Standard and Enterprise.<sup>2</sup>

Standard Edition comprised the following components:

- Oracle9iAS Portal
- Oracle HTTP Server *Powered by Apache* (OHS)  
(Apache 1.3 and Apache JServ with mod\_jserv, mod\_plsql, mod\_ssl, mod\_perl, mod\_ose, Perl Interpreter and JDK)
- Oracle Enterprise Java Engine  
(Support for Servlets, Java Server Pages, Enterprise Java Beans, Entity Beans and Business Components for Java (BC4J))
- Oracle9i File System  
(An Internet file system presenting documents and media as files and folders for users to access through Windows, HTTP, FTP and e-mail)
- Oracle9iAS Developer Kits  
(Developer kits for XML, database client and LDAP client)
- Oracle Enterprise Manager (OEM)  
(The base version of the browser-based management environment)

Enterprise Edition extended Standard Edition with the following components:

- Oracle9iAS Web Cache  
(Web and database caching for increased performance)
- Oracle9iAS Discoverer  
(Browser-based access to Oracle Discoverer for ad-hoc database queries)
- Oracle9iAS Forms Services  
(Browser-based access to Oracle Forms applications)
- Oracle9iAS Reports Services  
(Browser-based access to Oracle Reports)

Standard Edition contained the components sufficient to build our public website.

## 1.5 Product Versions

The table below illustrates how Oracle9iAS itself was a comparatively new product, first released in August 2000. Oracle9iAS Portal had a longer pedigree, as the successor to “WebDB 2.2”. Although version 3 of WebDB had been anticipated, it was actually the Early Adopter edition of Oracle9iAS Portal (3.0.6) that appeared in September 2000. The first production version (3.0.7) was released at the end of 2000.

	Server	WebDB	Portal	iAS
Jul 1998	Oracle8 (8.0.5)			
Oct 1998				
Feb 1999		WebDB 2.0		
Mar 1999	Oracle8i (8.1.5)			
Apr 1999				
Jul 1999		WebDB 2.1		
Sep 1999	Oracle8 (8.0.6)			
Oct 1999				
Dec 1999		WebDB 2.2		
Jan 2000	Oracle8i (8.1.6)			
May 2000				
Aug 2000				IAS 8i 1.0.1
Sep 2000			9iAS Portal 3.0.6	
Nov 2000	Oracle8i (8.1.7)			9iAS 1.0.2
Dec 2000			9iAS Portal 3.0.7	
Mar 2001				9iAS 1.0.2.1
Apr 2001			9iAS Portal 3.0.8	
May 2001			9iAS Portal 3.0.9	9iAS 1.0.2.2

Table: Oracle Product Release Dates for Windows NT

Our installation (at the start of 2001) therefore baselined with these product versions:

- Oracle8i Server 8.1.7.0.0
- Oracle9iAS Portal 3.0.7
- Oracle9iAS 1.0.2

## **1.6 High-Level Risk Analysis**

### **1.6.1 Business View**

The business view was that, once the website was live, the three risks were reputation, revenue and legal. Hackers or rivals must not compromise the privacy of customers' personal data (confidentiality). Outsiders must not be allowed to take over content management of the site (integrity). The website must not be down during TV and radio advertising campaigns (availability). Single loss expectancy could easily have exceeded the total cost of building the website.

We also had the business issues (carrying 100% risk) of lack of experience and budget. We did not have sufficient security experience within the company. We did not have sufficient Java experience within the company to complete the custom coding and integration work by ourselves. Since the product was so new, no-one could have had any real-world experience of deploying a website built using Oracle9i AS Portal. At the start of the project we did not have sufficient budget for all the components on our wishlist.

### **1.6.2 Risks and vulnerabilities**

The primary threat vectors <sup>3</sup> were:

- Outsider attack from the Internet
- Attack from malicious code
- Insider attack from our LAN
- Insider attack on the physical system

Apart from the business risks, the other risks were separated into network, host and application risks <sup>4</sup> (i.e. the Oracle software), as outlined below.

#### **1.6.2.1 Network**

- Attacks on our DNS.
- Denial of service (DOS) attacks.
- Eavesdropping of customers' personal and transaction data sent over the Internet.

#### **1.6.2.2 Host**

- The vulnerabilities of unhardened Windows NT servers.
- Hardware availability (requiring at least one working database server and one working webserver).

### 1.6.2.3 Application

- The vulnerabilities of the Oracle software, plus additional vulnerabilities introduced by patches or upgrades.
- Access via extraneous files (such as examples or feature demonstrations).
- Privileged access to Portal or to the database using default passwords (leading to exposure of customer data).
- Defacement of the website through external content management.
- Loss of the authoritative copy of the website.
- Software availability (requiring at least one active database server and at least one active webserver).

© SANS Institute 2003, Author retains full rights.

## **2. During Snapshot**

### **2.1 Business Issues**

#### 2.1.1 Experience

We transferred risk for security oversight to a well-known security consultancy, which have remained our advisers since the build. I also attended the SANS Kick Start and Security Essentials tracks (New Orleans 2001).

Since we had little experience of Java web programming at the time, we worked with a local software house. The software house had used Java and JSPs to deliver a graphical system to a major public utility. In order to qualify them for our project, all three departments (E-Commerce, Computer Services and Sales & Marketing) made site visits to interview them and inspect their offices and development procedures. Since they were a small firm and a new supplier, we insisted on regular code drops including sources and documentation.

As the product was so new, Oracle pre-sales consultants acted as mentors and advisers throughout the project and we paid for Oracle consultants to work with the software house. We also made use of Oracle Support.

#### 2.1.2 Budget

Since it was clear that the entire wishlist was not going to fit within budget, we costed both the ideal solution and a scaled down version. This “minimum compliant architecture” included the development and test systems, met the business needs and could be extended gradually toward the ideal solution.

For example, a major budget item was Oracle licences. Since Oracle9i AS was initially licensed by CPU power, we used a number of smaller web servers (with the option of a CPU upgrade and with room for a second CPU and more memory). This move also increased overall availability of the web servers.

### **2.2 Risks**

#### 2.2.1 Network

We transferred the risk for DNS hosting to our ISP and their DNS Support Team.



We chose to use a number of smaller firewalls to isolate the E-Commerce systems from both the LAN and the Internet. As well as reducing the costs of hardware and licensing, this gave us the opportunity to lock down a short, well tested security policy for the Internet-facing firewalls, whilst being able to customise and adapt a second policy for the LAN-facing firewalls.

To help protect against DOS attacks, on the Internet-facing firewalls we disabled ICMP and HTTP PUT and we configured Check Point's protection systems against address spoofing and SYN flooding attacks. (On the web servers we used BlackICE to drop hostile HTTP connections.)

To protect sensitive customer data transmitted over the Internet, we installed 40-bit (rather than 128-bit) SSL certificates <sup>5</sup> on our Oracle9i AS servers.

### 2.2.2 Hosts

The Technical Development Team hardened all the Windows NT servers and installed BlackICE. They configured limited accounts for the Service Desk to run tape backups. The only web access permitted from the servers was for each web server to surf itself.

Our design made extensive use of hardware RAID. We tried to avoid single points of failure and, indeed, the main Oracle database server was actually a hardware cluster with shared disks. All hardware and software items were put on maintenance and we established a small spares holding of common items (disks, fans, etc.). To ensure that the Service Desk would be alerted in case of device failure, Compaq Insight Manager was configured on the servers. Thus a console within the website could collect and log SNMP health data and send SMTP alerts to the email server on the LAN.

Load balancers did not make it into the "minimum compliant architecture". Instead we started off with round-robin DNS on our ISP's DNS servers: once a customer landed on a web server (www), OHS would redirect them to that web server by its own name (www1, www2, etc.). The business accepted the risk that if the first web server was down the customer might not try a second time!

When we later had the budget for load balancers, we had two main choices: licence the functionality of Check Point's ConnectControl on the internet-facing firewalls or install "black-box" load balancers. Although ConnectControl could have done the job, we chose to install F5 servers running BIG/IP because they would be able to monitor a range of services on each web server to determine responsiveness (for example, both JServ on port 8007 and OHS on port 80).

To address disaster recovery (DR) for our database-driven website, we installed a half-system at the DR site (a pair of web servers with a server for an Oracle standby database) and a private leased line. In normal operation the web servers at the DR site ran from the database at the main site whilst the archive logs were trickle-fed to the Oracle standby database. This meant that we could survive the failure of all the web servers at one site or the other (i.e. either www1/3/5/7 or www2/4) and that during a DR event, we could open the standby database to run a service at reduced capacity. Had we decided to encrypt the Oracle traffic on the leased line to the DR site, we had the choice of using either the feature set of our Cisco routers or, at extra cost, the functionality of the firewalls.

Only the Technical Development Team and the Service Desk had (unaccompanied) physical access to the computer rooms at the main site and the DR site.

### 2.2.3 Application

#### 2.2.3.1 Installation and hardening

We took the opportunity to rehearse installing the application, not only on our own PCs but also with our development and test systems on the LAN. I had been noting relevant vulnerabilities to Oracle8i and Oracle9i AS: by January 2001 there were already eight (numbered V1-V8 at Appendix 1).

On the production kit, we performed our tailored Oracle8i and Oracle9i AS installations and hardened the application software, as described in the checklist at Appendix 2. Later on, all further patches and upgrades were similarly rehearsed and documented.

#### 2.2.3.2 Access via extraneous files

As part of the hardening process we removed the demonstration files, help files and release documents from the web root of OHS, to prevent them being crawled and appearing in search engine listings. These demonstration files could have been targets for reconnaissance and later vulnerabilities, for example the Perl CGI, printenv, in the directory, oracle\iSuites\Apache\Apache\cgi-bin. However, during rehearsals we discovered that certain upgrades (for example, from Portal 3.0.7 to 3.0.9) restored these files.

#### 2.2.3.3 Privileged access through default passwords

Users in WebDB had been Oracle database users: for example, logging into WebDB as SCOTT/TIGER meant that you had just logged into the production database as SCOTT. A major change with Oracle9i AS Portal meant that you logged into Portal as a

lightweight SSO user, and then Portal itself logged into the database (as one of a number of controlled database users).

For the default portal name of PORTAL30, there were five database users whose passwords needed to be changed (both in the database and on the portal configuration page):

```
PORTAL30/PORTAL30
PORTAL30_PUBLIC/ PORTAL30_PUBLIC
PORTAL30_SSO/PORTAL30_SSO
PORTAL30_SSO_PUBLIC/ PORTAL30_SSO_PUBLIC
PORTAL30_DEMO/ PORTAL30_DEMO
```

We used the ISS Database Scanner for Oracle to review other weak and well-known database passwords. We also changed the default passwords for the two matching lightweight SSO superusers:

```
PORTAL30/PORTAL30
PORTAL30_SSO/PORTAL30_SSO
```

#### 2.2.3.4 Passwords for content managers and customers

It would have been very simple to configure the SSO password security settings to demand long, alphanumeric password that expired frequently. Whilst it appeared ideal to impose this level of security on the content managers, the same password requirements would have applied to the thousands of customers registering with our website. To get around this, what we did was to have the customers log into a Java application (which handled their personal account details within the database) and have the Java application automatically log them into a group in Portal. Since each group login only had a slightly different read-only view of the same Portal content, exposure of the group passwords was not considered vital. However, we also configured OHS to deny access to certain Portal URLs from outside the LAN, ensuring that only content managers on the LAN could reach the pages for manual login.

#### 2.2.3.5 Authoritative copy of the website

The beauty of the webserver was that they took their Portal content by logging into the Oracle database and their Java content from a single Java archive file (JAR or EAR). Backing up the webserver to CDROM meant a two-CD restore (one for Windows and Oracle9i AS, the other for the latest JAR or EAR file).

Having a number of Portal content managers on the LAN, the authoritative copy of [the Portal portion of] the website was whatever was currently stored in the production Oracle database.<sup>6</sup> What we did was to configure version control in Portal so that we could revert individual content items without resort to the database backup tapes.

### 2.2.3.6 Software availability

Having had problems with the reliability of external URL monitoring services for the web servers, we gave the Service Desk a PC that just showed a view of the monitoring screen for BIG/IP (to show which components on which web servers were responding).

We decided to configure the LAN-facing firewalls to permit the main OEM console on the LAN to communicate with the agents on the three database servers for database monitoring and alerting.

Had we wanted the OEM console to run batch jobs on any of the servers, then we should have had to assess the risk of creating special Windows NT accounts for their OEM intelligent agents. These accounts would have required additional privileges ("Logon Locally" or Administrator; "Logon as a batch job"; "Logon as a service"; member of the ORA\_DBA group) and a password that did not expire.

During the development process, we were able to perform extensive load testing on the production systems to help us tune the Portal caching and to determine the maximum performance of the "minimum compliant architecture".

## **2.3 Vulnerability assessment**

Before going live, we inspected our security footprint. The domain name registrations gave little away, and nmap showed that we were only exposing ports 80 and 443 on the Internet-facing firewalls. We used various pieces of software to try URLs on the website, to inspect the cookies and session ids and to demonstrate that the IDS was functioning.

As part of this testing, I observed vulnerability V11 (Appendix 1). Simply by changing the flag at the end of a Portal URL (from "\_mode=3" to "\_mode=2"), a public user gained access to the navigator screen to browse all objects on the website, to view user log details and to export modules. I raised a fault with Oracle and made sure that the patch was backported to our version of Portal.

As a final confidence check, a team from our security consultancy ran a vulnerability scan of the website (uncovering nothing harmful).

## **3. After Snapshot**

### **3.1 Live Website**

When the website went live in the middle of 2001, the Computer Services Department adopted it. The Technical Development Team took on the responsibility for researching vulnerabilities and testing and applying further patches (including the upgrade to Portal 3.0.9).

Since launch the “minimum compliant architecture” has built up enough to include most items on the wishlist, including a strong, commercial load-testing tool fully compatible with Portal and regularly scheduled external vulnerability scans.

### **3.2 Additional Complications**

We started out with a single firewall management console (with RAID and its own tape backup unit). Had we switched over to run from the DR site for an extended period back then, we would have been operational only until one of the firewalls needed its security policy changing.

The business has accepted that it takes time to load Java releases or reconfigure OHS because, the way we have locked down the infrastructure, staff have to visit each webserver at the main site and the DR site. The business has also accepted that content management is only possible from the LAN.

Oracle later changed the licensing structure for Oracle9i AS, basing it on the number of CPUs instead of their size or power. This meant that for us to improve performance, it became cheaper to replace a single-CPU webserver with a faster model than to licence the software for a second (slower) CPU or add an additional webserver.

### **3.3 Lessons Learned During Development**

#### **3.3.1 Working inside the envelope**

One of the plus points of Oracle9iAS had been a one-click installation of the infrastructure of our website. However, any components, configurations or version upgrades outside this envelope were not supported by Oracle. Two such examples were the version of Apache (in OHS) and the version of J2EE.

Firstly, whilst the current version of Apache in February 2001 was 1.3.19, Oracle HTTP Server *Powered by Apache* (OHS) was still powered by Apache 1.3.12.0.0.a from February 2000. A secondary issue was that we were unable to use third-party tools such as Comanche to help configure such an old version.

The second example was that we wanted to run some of our Java code inside Oracle9iAS but outside Portal and its Java development kit. We struggled to configure the Oracle Servlet Engine (OSE) for our needs and found that Oracle's JServ was too old to support the 2.2 Servlet API. Instead we had to supplement JServ (required by Portal) with Jakarta Tomcat (to run our Java code). Oracle caught up in a later release, introducing a new J2EE engine, Oracle Containers for Java (OC4J).

Conversely, if there were unwanted components inside the envelope we either had to configure them out or keep them patched and up-to-date (for example, the XSQL Servlet – V6 at Appendix 1). If we decided to configure them out, we had to be sure of the dependencies of other sub-components.

#### **3.3.2 Support**

As customers with paid support, we could use Oracle's Metalink website to search for patches and bugs and to raise electronic fault reports (iTARs). The first problem was that every single sub-component of Oracle9iAS was listed separately, so it meant regular trawls through Metalink to keep up-to-date. The second problem was that, once a bug was diagnosed, it would be fixed at a subsequent release. Only if a good business case could be made might Oracle backport the fix for an older release.

#### **3.3.3 Transition to Live**

If using a traditional development process, i.e. transferring the site from a development system through a test system to the live system, then each transfer required a multi-stage export/import sequence for the Portal content. We reported an iTAR for the process of exporting/importing folder portlets and sub-pages and Patch #1727108 was back-ported to Portal 3.0.7 for us in due course.

However, this import also had some unwanted side effects: firstly, ownership of all pages and sub-pages changed to the portal owner, default PORTAL30. Secondly, all lightweight SSO users had their personal details purged and their passwords reset to their username in uppercase. Had we been using SSO for our customers this would have been a major problem.

Since it was only possible to export/import between systems running exactly the same version of Oracle9iAS Portal, the development, test and live systems had to be kept in step.

An alternative process would have been to backup the whole database and move it across or to develop the site in-place, on the live system, using version control and manual content release.

### 3.3.4 Resources for Web Developers

A Portal website is not like a standard website: content and structure are embedded in a proprietary environment. Web developers who are already familiar with tools like Dreamweaver and FrontPage are faced with foreign concepts (such as portlets, folders, regions, pages, categories and perspectives). So many books that promise "Oracle and the Internet" still refer to obsolete products, such as OAS and WebDB. The best source of information for Oracle9iAS Portal is the Oracle web site, with its manuals and whitepapers, discussion forums and online presentations. After we had gone live, ideal reference was published

### **3.4 Reflection on SANS Material**

Had I not attended the SANS training, it would have been much more difficult for me to have raised awareness of the security risks of hosting our own database-driven website. Particular aspects included an understanding of the threat, the practicalities of hardening Windows NT and the need for an IDS (even though we had firewalls).

Without this knowledge, backed up by concrete examples, it would have been impossible to justify the time and budget required for the security activities. We could then have ended up exposing servers to the Internet running, if not a standard build of Windows NT, then certainly an unmodified copy of Oracle9iAS.

## References

- [1] Oracle. "Oracle9i AS v1.0.2.2 Technical Info". 2002. URL: <http://otn.oracle.com/products/ias/techlisting.html> (20 May 2003)
- [2] Oracle. "Oracle9i Application Server (Oracle9i AS) Summary of Standard, Enterprise and Wireless Edition Features (v1.0.2.1)". April 2001. URL: <http://otn.oracle.com/products/ias/pdf/9iaspackaging.pdf> (20 May 2003)
- [3] The SANS Institute. Intrusion Detection: The Big Picture. New Orleans: The SANS Institute, 2001. 6-35.
- [4] The SANS Institute. Information Security: The Big Picture. New Orleans: The SANS Institute, 2001. 1-26.
- [5] Lowenthal, Bruce. "Best Practices in HTTP Security." 05 June 2001. 12. URL: [http://otn.oracle.com/product/ias/pdf/best\\_practices/security\\_best\\_practices.PDF](http://otn.oracle.com/product/ias/pdf/best_practices/security_best_practices.PDF). (20 May 2003)
- [6] Allen, Julia H. The CERT Guide to System and Network Security Practices. Boston: Addison-Wesley, 2001. 114.



## Appendix 1: Relevant Vulnerabilities (October 2000 - May 2001)

<b>Vulnerability V1</b>	Listener allows overwrite or append to any file.
<b>Published</b>	October 2000, Internet Security Systems (ISS) X-Force.
<b>Exploit</b>	<a href="http://xforce.iss.net/alerts/advise66.php">http://xforce.iss.net/alerts/advise66.php</a>
<b>Solutions</b>	<p>Although fixed at Oracle8i 8.1.7.0.0, a flag in the "listener.ora" file ("ADMIN_RESTRICTIONS_&lt;listener_name&gt;") must be set to ON. Its default value is OFF. Oracle also recommend establishing the listener password in this mode of operation, where the default listener password is blank.</p> <p><a href="http://technet.oracle.com/deploy/security/pdf/listener_alert.pdf">http://technet.oracle.com/deploy/security/pdf/listener_alert.pdf</a>  <a href="http://xforce.iss.net/static/5380.php">http://xforce.iss.net/static/5380.php</a></p>
<b>Fixed at version</b>	Oracle8i 8.1.7.0.0, but flag needs to be set.
<b>Vulnerability V2</b>	Configuration web page not password protected.
<b>Published</b>	<b>December 2000, Michal Zalewski</b>
<b>Exploit</b>	<p><a href="http://archives.neohapsis.com/archives/bugtraq/2000-12/0339.html">http://archives.neohapsis.com/archives/bugtraq/2000-12/0339.html</a>  <a href="http://archives.neohapsis.com/archives/bugtraq/2000-12/0372.html">http://archives.neohapsis.com/archives/bugtraq/2000-12/0372.html</a></p>
<b>Solutions</b>	<p>Oracle recommends restricting this to legitimate users using the "administrators=" setting in the wdsvr.app file, so preventing public users from altering or deleting the Database Access Descriptor (DAD) from a browser as a denial of service.</p> <p><a href="http://archives.neohapsis.com/archives/bugtraq/2000-12/0463.html">http://archives.neohapsis.com/archives/bugtraq/2000-12/0463.html</a>  <a href="http://technet.oracle.com/deploy/security/pdf/webdb_bugpost.pdf">http://technet.oracle.com/deploy/security/pdf/webdb_bugpost.pdf</a></p> <p>SAINT checks for this vulnerability (<a href="http://www.wwdsi.com/cgi-bin/doc.pl?document=vulnerability/Oracle_vulnerabilities">http://www.wwdsi.com/cgi-bin/doc.pl?document=vulnerability/Oracle_vulnerabilities</a>).</p>
<b>Fixed at version</b>	Oracle9iAS Portal 3.0.8

Vulnerability V3	Passwords visible in configuration file (wdbsvr.app).
Published	<b>(consequential)</b>
<b>Exploit</b>	The Database Access Descriptor (DAD), i.e. the database username and password of the portal owner and single sign-on owner, is stored in clear in the file, wdbsvr.app. Local access or directory traversal vulnerability may expose these details.
<b>Solutions</b>	Password is encrypted at 3.0.8
<b>Fixed at version</b>	Oracle9iAS Portal 3.0.8

Vulnerability V4	Injection of PL/SQL code or procedure calls into URL.
Published	<b>December 2000, Michal Zalewski</b>
<b>Exploit</b>	<a href="http://archives.neohapsis.com/archives/bugtraq/2000-12/0339.html">http://archives.neohapsis.com/archives/bugtraq/2000-12/0339.html</a> <a href="http://archives.neohapsis.com/archives/bugtraq/2000-12/0372.html">http://archives.neohapsis.com/archives/bugtraq/2000-12/0372.html</a> <a href="http://archives.neohapsis.com/archives/bugtraq/2000-12/0373.html">http://archives.neohapsis.com/archives/bugtraq/2000-12/0373.html</a> <a href="http://archives.neohapsis.com/archives/bugtraq/2000-12/0395.html">http://archives.neohapsis.com/archives/bugtraq/2000-12/0395.html</a> <a href="http://archives.neohapsis.com/archives/bugtraq/2000-12/0431.html">http://archives.neohapsis.com/archives/bugtraq/2000-12/0431.html</a> <a href="http://archives.neohapsis.com/archives/bugtraq/2000-12/0439.html">http://archives.neohapsis.com/archives/bugtraq/2000-12/0439.html</a> <a href="http://archives.neohapsis.com/archives/bugtraq/2000-12/0449.html">http://archives.neohapsis.com/archives/bugtraq/2000-12/0449.html</a>
<b>Solutions</b>	<p>One of:</p> <p>A. Revoke public access to procedures (such as OWA, SYS and DBMS) which can potentially execute user-specified SQL statements.</p> <p>B. Disable access to URLs which match certain criteria by adding rules to the plsql.conf file:</p> <pre>&lt;Location /pls/*/ABCD.*&gt;   SetHandler pls_handler   <b>Order deny,allow</b>   Deny from all &lt;/Location&gt;</pre> <p>where ABCD is the name of the procedure or synonym, and the rule must be repeated for all permutations of lower, upper and mixed case.</p> <p><a href="http://technet.oracle.com/deploy/security/pdf/webdb_bugpost.pdf">http://technet.oracle.com/deploy/security/pdf/webdb_bugpost.pdf</a>  <a href="http://archives.neohapsis.com/archives/bugtraq/2000-12/0463.html">http://archives.neohapsis.com/archives/bugtraq/2000-12/0463.html</a></p> <p>SAINT checks for this vulnerability (<a href="http://www.wwdsi.com/cgi-bin/doc.pl?document=vulnerability/Oracle_vulnerabilities">http://www.wwdsi.com/cgi-bin/doc.pl?document=vulnerability/Oracle_vulnerabilities</a>).</p>

	<p>Oracle Patch #1554571 for mod_plsql version 3.0.0.8.3 introduces a new configuration parameter in mod_plsql called "exclusion_list". This parameter can be used to disallow URLs with specific formats from being passed to mod_plsql; by default it excludes URLs with special characters such as space, tab, newline, carriage return, single quote, and backslash.</p> <p><a href="http://metalink.oracle.com/">http://metalink.oracle.com/</a>  <a href="http://archives.neohapsis.com/archives/bugtraq/2001-01/0206.html">http://archives.neohapsis.com/archives/bugtraq/2001-01/0206.html</a></p>
<b>Fixed at version</b>	Oracle9iAS Portal 3.0.8

<b>Vulnerability V5</b>	mod_plsql error message cannot be configured.
<b>Published</b>	<b>December 2000, Michal Zalewski</b>
<b>Exploit</b>	<p>Error messages from mod_plsql (rather than 404 pages) have been crawled, such that a simple search engine query locates the signature of WebDB, OAS and Portal installations:</p> <p><a href="http://www.google.com/search?q=procedure+dad+environment+%22ora-06550%22+url">http://www.google.com/search?q=procedure+dad+environment+%22ora-06550%22+url</a></p> <p><a href="http://archives.neohapsis.com/archives/bugtraq/2000-12/0339.html">http://archives.neohapsis.com/archives/bugtraq/2000-12/0339.html</a></p>
<b>Solutions</b>	None
<b>Fixed at version</b>	

<b>Vulnerability V6</b>	<b>Oracle XSQL Servlet accepts external XML style sheets.</b>
<b>Published</b>	<b>January 2001, Georgi Guninski</b>
<b>Exploit</b>	<a href="http://www.guninski.com/oraxsql.html">http://www.guninski.com/oraxsql.html</a> <a href="http://archives.neohapsis.com/archives/win2ksecadvice/2001-q1/0018.html">http://archives.neohapsis.com/archives/win2ksecadvice/2001-q1/0018.html</a>
<b>Solutions</b>	<p>One of:</p> <p>The new release of XSQL Servlet (1.0.4.1) can be obtained from Oracle Technology Network at  <a href="http://technet.oracle.com/software/tech/xml/xsql_servlet/software_index.htm">http://technet.oracle.com/software/tech/xml/xsql_servlet/software_index.htm</a>  <a href="http://technet.oracle.com/deploy/security/pdf/xsql_alert.pdf">http://technet.oracle.com/deploy/security/pdf/xsql_alert.pdf</a>  <a href="http://archives.neohapsis.com/archives/bugtraq/2001-01/0364.html">http://archives.neohapsis.com/archives/bugtraq/2001-01/0364.html</a></p> <p>B. Patch the database up to 8.1.7.1.1  <a href="http://metalink.oracle.com/">http://metalink.oracle.com/</a></p>
<b>Fixed at version</b>	XSQL Servlet 1.0.4.1 (included in Oracle8i 8.1.7.1.1)

<b>Vulnerability V7</b>	<b>Directory traversal vulnerability in JSP/SQLJSP.</b>
<b>Published</b>	<b>January 2001, Georgi Guninski.</b>
<b>Exploit</b>	<a href="http://www.guninski.com/orajsp.html">http://www.guninski.com/orajsp.html</a> <a href="http://archives.neohapsis.com/archives/win2ksecadvice/2001-q1/0028.html">http://archives.neohapsis.com/archives/win2ksecadvice/2001-q1/0028.html</a>
<b>Solutions</b>	<p>An updated version of OJSP (1.1.2.2.0) is available on the Oracle Technology Network at  <a href="http://technet.oracle.com/tech/java/servlets/index.htm">http://technet.oracle.com/tech/java/servlets/index.htm</a>  <a href="http://technet.oracle.com/deploy/security/pdf/jspdocroot_alert.pdf">http://technet.oracle.com/deploy/security/pdf/jspdocroot_alert.pdf</a>  <a href="http://archives.neohapsis.com/archives/bugtraq/2001-02/0239.html">http://archives.neohapsis.com/archives/bugtraq/2001-02/0239.html</a></p>
<b>Fixed at version</b>	OJSP 1.1.2.0.0

<b>Vulnerability V8</b>	<b>JSP/SQLJSP allows unintended execution of .jsp in a similar directory path outside the web root.</b>
<b>Published</b>	<b>January 2001, Georgi Guninski.</b>
<b>Exploit</b>	<a href="http://www.guninski.com/orajsp.html">http://www.guninski.com/orajsp.html</a> <a href="http://archives.neohapsis.com/archives/win2ksecadvice/2001-q1/0028.html">http://archives.neohapsis.com/archives/win2ksecadvice/2001-q1/0028.html</a>
<b>Solutions</b>	<p>Ensure that the virtual path in a URL is different from the actual directory path when using Oracle Apache/JServ. Do not use the &lt;servletzonepath&gt; directory in "ApJServMount &lt;servletzonepath&gt; &lt;servletzone&gt;" to store data or files.</p> <p> <a href="http://technet.oracle.com/deploy/security/pdf/jspexecute_alert.pdf">http://technet.oracle.com/deploy/security/pdf/jspexecute_alert.pdf</a>  <a href="http://archives.neohapsis.com/archives/bugtraq/2001-02/0240.html">http://archives.neohapsis.com/archives/bugtraq/2001-02/0240.html</a> </p>
<b>Fixed at version</b>	Oracle9iAS 1.0.2.1

<b>Vulnerability V9</b>	Access is possible outside the web root if "FilePermission" is granted to <<ALL FILES>>.
<b>Published</b>	<b>February 2001.</b>
<b>Exploit</b>	<a href="http://technet.oracle.com/deploy/security/pdf/ojvm_alert.pdf">http://technet.oracle.com/deploy/security/pdf/ojvm_alert.pdf</a> <a href="http://archives.neohapsis.com/archives/bugtraq/2001-02/0255.html">http://archives.neohapsis.com/archives/bugtraq/2001-02/0255.html</a>
<b>Solutions</b>	Oracle's recommended fix is to grant permission specifically to the document root path and not to the '<<ALL FILES>>' wildcard.
<b>Fixed at version</b>	

<b>Vulnerability V10</b>	Apache Listener stops responding after prolonged use of mod_plsql.
<b>Published</b>	March 2001, Oracle9iAS 1.0.2.1 Release Notes (NT/2000).
<b>Exploit</b>	Intermittently the Apache listener stops responding within two to three days after prolonged use of mod_plsql.
<b>Solutions</b>	Restart the Apache listener
<b>Fixed at version</b>	

<b>Vulnerability V11</b>	Portal user gains access to site structure.
<b>Published</b>	May 2001.
<b>Exploit</b>	Changing the “mode” parameter of a Portal URL, from <a href="http://www.portal307.com/servlet/page?_pageid=250&amp;_dad=portal30&amp;_sc_hema=PORTAL30&amp;_mode=3">http://www.portal307.com/servlet/page?_pageid=250&amp;_dad=portal30&amp;_sc_hema=PORTAL30&amp;_mode=3</a> to <a href="http://www.portal307.com/servlet/page?_pageid=250&amp;_dad=portal30&amp;_sc_hema=PORTAL30&amp;_mode=2">_mode=2</a> allows access to browse all objects on a site, view user log details and export modules.
<b>Solutions</b>	Patch backported to Oracle9iAS Portal 3.0.7 as patch #1764569 <a href="http://metalink.oracle.com/">http://metalink.oracle.com/</a>
<b>Fixed at version</b>	Oracle9iAS Portal 3.0.9

Compiled 18 May 2001.

## Appendix 2: Oracle9iAS Portal 3.0.7 Configuration Checklist

1. Configure Oracle8i database
  - Set ADMIN RESTRICTIONS <listener name>=ON in listener.ora file
  - Upgrade Oracle8i to 8.1.7.1.1 (including XSQL Servlet 1.0.4.1)
2. Configure Oracle9iAS
  - Install OJSP 1.1.2.2.0
  - Set administrators= flag in wdbsvr.app file
  - Edit plsql.conf file to deny external access to OWA, SYS and DBMS procedures and synonyms
  - Apply Oracle patch #1554571 (mod plsql exclusion list)
  - Apply Oracle patch #1727108 (export/import)
  - Apply Oracle patch #1764569 (mode=2 access to site structure)
3. Configure passwords
  - Change database passwords and settings
    - Alter well-known passwords of privileged users  
SYS/CHANGE\_ON\_INSTALL  
SYSTEM/MANAGER  
AURORA\$ORB\$UNAUTHENTICATE/INVALID  
CTXSYS/CTXSYS  
DBSNMP/DBSNMP  
MDSYS/MDSYS  
ORDPLUGINS/ORDPLUGINS  
ORDSYS/ORDSYS  
OUTLN/OUTLN
    - Delete demo users  
ADAMSWOOD  
BLAKE/PAPER  
CLARK/CLOTH  
JONES/STEEL  
SCOTT/TIGER
    - Alter default passwords of Portal users  
PORTAL30/PORTAL30  
PORTAL30\_PUBLIC/ PORTAL30\_PUBLIC  
PORTAL30\_SSO/PORTAL30\_SSO  
PORTAL30\_SSO\_PUBLIC/ PORTAL30\_SSO\_PUBLIC  
PORTAL30\_DEMO/ PORTAL30\_DEMO
    - Enable auditing of failed login attempts

- Update Portal Database Access Descriptor (DAD)
- Change Portal SSO passwords and settings
  - Change SSO passwords of Portal & SSO owners  
PORTAL30/PORTAL30  
PORTAL30\_SSO/PORTAL30\_SSO
  - Configure SSO password policy

4. Configure OHS (Apache)

- Perl printenv
- Demo files
- Help
- Documentation

© SANS Institute 2003, Author retains full rights.





# Upcoming SANS Training

[Click Here for a full list of all Upcoming SANS Events by Location](#)

Security Operations Center Summit & Training	Washington, DCUS	Jun 05, 2017 - Jun 12, 2017	Live Event
SANS Houston 2017	Houston, TXUS	Jun 05, 2017 - Jun 10, 2017	Live Event
SANS San Francisco Summer 2017	San Francisco, CAUS	Jun 05, 2017 - Jun 10, 2017	Live Event
SEC555: SIEM-Tactical Analytics	San Diego, CAUS	Jun 12, 2017 - Jun 17, 2017	Live Event
SANS Milan 2017	Milan, IT	Jun 12, 2017 - Jun 17, 2017	Live Event
SANS Charlotte 2017	Charlotte, NCUS	Jun 12, 2017 - Jun 17, 2017	Live Event
SANS Secure Europe 2017	Amsterdam, NL	Jun 12, 2017 - Jun 20, 2017	Live Event
SANS Rocky Mountain 2017	Denver, COUS	Jun 12, 2017 - Jun 17, 2017	Live Event
SANS Minneapolis 2017	Minneapolis, MNUS	Jun 19, 2017 - Jun 24, 2017	Live Event
DFIR Summit & Training 2017	Austin, TXUS	Jun 22, 2017 - Jun 29, 2017	Live Event
SANS Paris 2017	Paris, FR	Jun 26, 2017 - Jul 01, 2017	Live Event
SANS Cyber Defence Canberra 2017	Canberra, AU	Jun 26, 2017 - Jul 08, 2017	Live Event
SANS Columbia, MD 2017	Columbia, MDUS	Jun 26, 2017 - Jul 01, 2017	Live Event
SEC564:Red Team Ops	San Diego, CAUS	Jun 29, 2017 - Jun 30, 2017	Live Event
SANS London July 2017	London, GB	Jul 03, 2017 - Jul 08, 2017	Live Event
Cyber Defence Japan 2017	Tokyo, JP	Jul 05, 2017 - Jul 15, 2017	Live Event
SANS Cyber Defence Singapore 2017	Singapore, SG	Jul 10, 2017 - Jul 15, 2017	Live Event
SANS Munich Summer 2017	Munich, DE	Jul 10, 2017 - Jul 15, 2017	Live Event
SANS Los Angeles - Long Beach 2017	Long Beach, CAUS	Jul 10, 2017 - Jul 15, 2017	Live Event
SANS ICS & Energy-Houston 2017	Houston, TXUS	Jul 10, 2017 - Jul 15, 2017	Live Event
SANSFIRE 2017	Washington, DCUS	Jul 22, 2017 - Jul 29, 2017	Live Event
Security Awareness Summit & Training 2017	Nashville, TNUS	Jul 31, 2017 - Aug 09, 2017	Live Event
SANS San Antonio 2017	San Antonio, TXUS	Aug 06, 2017 - Aug 11, 2017	Live Event
SANS Prague 2017	Prague, CZ	Aug 07, 2017 - Aug 12, 2017	Live Event
SANS Hyderabad 2017	Hyderabad, IN	Aug 07, 2017 - Aug 12, 2017	Live Event
SANS Boston 2017	Boston, MAUS	Aug 07, 2017 - Aug 12, 2017	Live Event
SANS Salt Lake City 2017	Salt Lake City, UTUS	Aug 14, 2017 - Aug 19, 2017	Live Event
SANS New York City 2017	New York City, NYUS	Aug 14, 2017 - Aug 19, 2017	Live Event
SANS Virginia Beach 2017	Virginia Beach, VAUS	Aug 21, 2017 - Sep 01, 2017	Live Event
SANS Chicago 2017	Chicago, ILUS	Aug 21, 2017 - Aug 26, 2017	Live Event
SANS Adelaide 2017	Adelaide, AU	Aug 21, 2017 - Aug 26, 2017	Live Event
SANS Atlanta 2017	OnlineGAUS	May 30, 2017 - Jun 04, 2017	Live Event
SANS OnDemand	Books & MP3s OnlyUS	Anytime	Self Paced