



Interested in learning  
more about security?

## SANS Institute InfoSec Reading Room

This paper is from the SANS Institute Reading Room site. Reposting is not permitted without express written permission.

### Black ICE 2.5 Events, False Positives and Custom Attack Signatures

The major challenge for administrators of Intrusion Detection Systems is distinguishing between events that are genuine malicious activity and those that are false positives. This paper aims to help BlackICE IDS administrators by identifying and classifying some events frequently seen by IDS agents in two common deployments - on a DMZ web server and on systems within an internal (mainly Microsoft) network. Network ICE do provide BlackICE event ('intrusion') descriptions in an online database [1], but many of these need...

Copyright SANS Institute  
Author Retains Full Rights



AD

## **Black ICE 2.5 Events, False Positives and Custom Attack Signatures**

Alan Mercer, GSEC Practical Version 1.2f

### **Introduction**

The major challenge for administrators of Intrusion Detection Systems is distinguishing between events that are genuine malicious activity and those that are false positives.

This paper aims to help BlackICE IDS administrators by identifying and classifying some events frequently seen by IDS agents in two common deployments – on a DMZ web server and on systems within an internal (mainly Microsoft) network.

Network ICE do provide BlackICE event ('intrusion') descriptions in an online database [1], but many of these need further research before they can be classified satisfactorily. This paper includes additional research into some common events.

The nature of BlackICE's detection engine means that certain generic events may be triggered by different attacks (e.g. the *HTTP field with binary* event). IDS administrators are encouraged to further research all reported events thoroughly and to not assume event X is a result of attack Y.

The last section of the paper covers an unsupported method of creating custom BlackICE attack signatures that may prove useful in certain circumstances. A custom attack signature could be used to detect a new attack in the period between the attack being first identified and the vendor releasing an official attack signature update.

Please note that an in-depth discussion of incident handling and response procedures is not part of this research. Other papers available from SANS [2] address such issues.

### **BlackICE IDS Agent Configurations**

These investigations were made using the Enterprise edition (version 2.5) of Network ICE's BlackICE product and not BlackICE Defender, the personal IDS and firewall. However certain sections are relevant, particularly the custom attack signature definition.

The Agents used in this research were host-based BlackICE Agent for Server 2.5ev and BlackICE Agent for Workstation 2.5ev running on Windows NT/2000. Both agents were reporting to an ICEcap console version 2.5eq. The network-based BlackICE Sentry agent was not used, though a Sentry agent will generate identical events when monitoring passing network traffic.

The Server agents were installed on Internet-facing DMZ IIS web servers offering both web and FTP services. The only traffic allowed into the DMZ from the Internet was on port 80 (Web), port 443 (Secure Web) and port 21 (FTP) to all machines.

Machines on the internal network were running both Server and Workstation agents.

## Common BlackICE events generated by Internet-facing IIS web servers agents

As soon as Internet-facing web servers are connected to the Internet they will bombard the IDS administrator with events to investigate and classify.

With only ports 21, 80 and 443 open most of the malicious activity will fall into 3 categories: web-based server attacks (e.g. Nimda worm, Code Red and IIS Printer buffer overflows), FTP activity and Operating System (O/S) fingerprinting attempts.

It is worth noting that if the IDS agents pick up activity on any ports other than ports 21, 80 and 443 it points to a misconfiguration of the firewall. For example some firewalls allow inbound/outbound DNS traffic to pass by default [3].

Note also that Workstation agent event descriptions are simpler than Server agent event descriptions. Certain Workstation agent events may have generic descriptions like **HTTP Attack**.

### Code Red Worm

The Code Red [4] worm hit the Internet around July 19th 2001 and after massive initial activity Code Red incidents have fallen away. Server agents report the following events when hit by various flavours of Code Red attack.

#### Original Code Red

##### **ISAPI Extension Overflow**

Parameters:  
length: 362  
URL: /default.ida  
arg: NNNNNNNN (cont.)

#### Code Red II (& Variants)

##### **ISAPI Extension Overflow**

Parameters:  
length: 362  
URL: /default.ida  
arg: XXXXXXXX (cont.)

#### eEye Code Red scan [5]

##### **ISAPI Extension Overflow**

Parameters:  
length: 222  
URL: /x.ida  
arg: AAAAA (cont.)

Though it is rarer to see Code Red II events anymore, attacks from Code Red still persist and will continue to do so for some time [6]. Note that unlike Nimda, Code Red attacks only trigger one BlackICE event per attack.

### Nimda Worm (and variants)

As Code Red activity started to subside a new and highly infectious worm, known as Nimda [7], struck the Internet around the 17th September 2001. From a very high initial attack rate, attack numbers have fallen, though Nimda-infected machines still account for a large proportion of incoming attacks

Black ICE agents report a number of events in response to Nimda attack. These events are generally triggered in batches of 4 from the same IP address over a 1-second interval. Repeated attack is common.

#### ***HTTP UTF8 backtick***

Parameters:

URL: = /scripts/../../../../winnt/system32/cmd.exe |  
/scripts/../../../../winnt/system32/cmd.exe

#### ***HTTP URL with double encoded ../***

Parameters:

URL: = /\_mem\_bin/../../../../../../../../winnt/system32/cmd.exe |  
/\_vti\_bin/../../../../../../../../winnt/system32/cmd.exe |  
/msadc/../../../../V...../...../...../winnt/system32/cmd.exe |  
/scripts/../../../../winnt/system32/cmd.exe

#### ***HTTP URL Scan***

Parameters:

URL: = /\_mem\_bin/../../../../../../../../winnt/system32/cmd.exe |  
/\_vti\_bin/../../../../../../../../winnt/system32/cmd.exe |  
/c/winnt/system32/cmd.exe | /d/winnt/system32/cmd.exe

#### ***IIS System 32 Command***

Parameters:

URL: = /\_mem\_bin/../../../../../../../../winnt/system32/cmd.exe |  
/\_vti\_bin/../../../../../../../../winnt/system32/cmd.exe |  
/c/winnt/system32/cmd.exe | /d/winnt/system32/cmd.exe |  
/msadc/../../../../V...../...../...../winnt/system32/cmd.exe

Note these events are generic and can be triggered by attacks other than the Nimda worm.

### **IIS 5.0 Printer Buffer Overflow Attack**

Seen less frequently are attempts to exploit an IIS 5.0 buffer-overflow reported in May 2001 [8]. Like Nimda, these IIS printer buffer overflow attacks trigger more than one event. The event pairs, generated from 1 IP address at the same time, are

#### ***IIS .printer overflow***

Parameters:

length = 356  
URL= /NULL.printer

#### ***HTTP field with binary***

Parameters:

URL= /NULL.printer  
field\_length = 356 | 779  
binary\_count = 93 | 124

Note the ***HTTP field with binary*** event is a heuristic signature for the detection of buffer overflows and format string attacks. This event can therefore be generated in response to other types of attack, though as stated in the Network ICE support site the event often appears in pairs [9].

## Other malicious web activity

If web sites are using password authentication, failed attempts to access them will generate the following event

### ***HTTP login failed***

Parameters:

count = varies (see below)

login = URL being attacked (e.g. /extranet)

A query the Security event log on Windows system for failure audit events (logon type 2) will identify the account used for the failed logons.

## FTP Activity

It is likely that every day FTP scanning activity will be detected. Often attackers scan a ranges of IP addresses so if you have IDS agents installed on a number of Internet-facing machines you will see the following event reported over a short period of time from the same IP address by each agent in turn (assuming FTP services are not running).

### ***FTP port probe***

Parameters:

port = 21

reason = RSTsent or NOanswer

If your servers are hosting FTP services you may see attempts to guess legitimate passwords,

### ***FTP login failed***

Parameters:

count = 4

victim = IP Address

login = anonymous@ftp.microsoft.com

By default this event is generated after 4 failed logins in a configurable 3600-second period.

## O/S Fingerprinting

From time to time the Internet-facing machine will be OS fingerprinted [10] from another machine on the Internet. Such activity can trigger the following events.

### ***TCP OS fingerprint***

Parameters:

port = varies (e.g. 21, 80 etc depending on open ports)

flags = varies (e.g. SF, SFPU depends on fingerprinting method)

options = varies (e.g. 3-0x;2-0x01;8-0x3F3F3F3F000000)

### ***NMAP OS fingerprint***

Parameters:

port = varies (e.g. 21)

flags = varies (e.g. S)

options = varies (e.g. 3-0x;2-0x01;8-0x3F3F3F3F000000)

### **Common BlackICE false positives seen on an internal Microsoft network**

Unlike agents running on the DMZ web servers – exposed only to external attacks on port 21, 80 and 443 – agents running on an internal network will see a lot more activity across a broad range of ports. Identifying and classifying the nature of this activity – malicious or false positive – is a big challenge for IDS administrators.

Every internal network configuration is different so the purpose of this section is to point BlackICE IDS administrators in the general direction event classification. Ports used by different applications vary as much as the network activity generated by different applications.

Some of these events will be seen by DMZ server agents, though this will depend on the types of network traffic allowed into the DMZ from the internal network and other DMZs e.g. network backups, Enterprise monitoring systems etc.

Identifying and classifying these false positives allows the IDS administrator to use the built-in BlackICE facilities for managing false positives.

Such facilities include

- Using ICEcap policies to create policy issues that drop the severity of common false positive events.
- Defining trusted hosts, trusted issues and trust pairs (trusted issues from certain hosts) to prevent event generation in the first place.
- Modifying the thresholds beyond which an event is generated.

A discussion of these techniques is not covered in detail here.

### **Probes and Scans**

A port probe event is generated when a failed connection is made to a network service. The connection fails because the service is not running, is temporarily unavailable or a firewall rule on the IDS agent rejects the connection request.

#### ***HTTP port probe***

Parameters:

port = 80

reason = varies (e.g. RSTsent=connection rejected, Noanswer=no response)

*Cause:* Failed connections to TCP port 80.

*Example(s):* Windows 2000 can trigger these when mapping drives. Also seen if

web-based attacks (Nimda or Code Red) are directed against non-web DMZ servers.

***NetBIOS port probe***

Parameters:

port = 139

reason = varies (e.g. RST sent, No answer)

*Cause:* A connection to TCP port 139.

*Example(s):* Mapping a drive with 'Net Use' (or with Windows Explorer) to a machine when NetBIOS file and print services (on TCP 139) are unavailable.

***SNMP port probe***

Parameters:

port = 161

reason = varies (e.g. ICMP sent, Firewallled by Agent)

*Cause:* A failed connection to UDP port 161.

*Example(s):* Microsoft's SMS and Enterprise management and monitoring systems can generate many of these probes during data collection.

***TCP port probe & UDP port probe***

Parameters:

port = varies (port of service probed)

reason = varies (ICMP sent [UDP], RST sent [TCP], Firewallled, No answer)

*Cause:* Failed connections to services running on TCP/UDP ports that are unknown by the Black ICE agent.

*Example(s):* They will often be seen when legitimate services are too busy to respond to connection attempts. Examples include monitoring agents talking to collection servers, browsers connecting to busy secure web sites (TCP 443) and very commonly in Windows 2000 environments when machines probe the Direct Host port [11] or TCP 445.

***TCP port scan & UDP port scan***

Parameters:

port = varies (e.g. port 1 | port 2 | port 3 | port 4....)

reason = varies (ICMP sent [UDP], RST sent [TCP], Firewallled, No answer)

*Cause:* Triggered by a sequential connection to 4 unique TCP or UDP ports (this is configurable).

*Example(s):* Network backup agents communicating with backup servers or by network mapping tools.

**Microsoft networking activity**

***MS share dump***

Parameters:

(null)

*Example(s):* Seen frequently in a Microsoft domain environment - it can be

generated through browsing the share list on a domain machine in Network Neighbourhood.

***SMB empty password***

Parameters:  
account = varies  
share = \\MACHINENAME\SHARE

*Cause:* A connection made to a share with no password.

*Examples:* Automated services may connect to, say SMS or anti-virus update shares that have no password protection. Also seen if a user logged on with a Windows domain account connects to another Windows machine that is not part of the domain, but the credentials match local credentials (username and password).

***MS security ID lookup***

Parameters:  
(null)

*Example(s):* Normal domain activity including viewing user rights in User Manager, viewing logged on users in Server Manager and opening remote event logs.

***SMB login failed***

Parameters:  
count = varies (number of failed attempts - 4, 6 etc)  
login = e.g. Administrator  
victim = IP address

*Cause:* 4 failed logins within a configurable 3600-second period.

*Example(s):* Frequently seen if services (e.g. SMS, monitoring tools etc) are running as a user account and the password has changed or expired.

***MS name lookup***

Parameters:  
(null)

*Example(s):* Generated during domain member to domain controller communication. Viewing user details with a domain management tool like Hyena can generate it (along with an ***MS security ID lookup*** event).

**Network discovery/management activity**

***SNMP backdoor***

Parameters:  
community = varies (e.g. admin | openview | password etc)

*Cause:* SNMP connect to a machine with one of a list of default passwords.

*Example(s):* Your network uses default SNMP passwords

***SNMP discovery broadcast***

Parameters:



command = varies (e.g. community = public)

*Cause:* SNMP GET commands.

*Examples:* Enterprise management and monitoring systems broadcasts.

### **Other network activity**

#### ***ICMP subnet mask request***

Parameters:

(null)

*Examples:* Network management and monitoring discovery broadcasts.

#### ***RPC bad credentials***

Parameters:

reason = varies (e.g. credlen&length=500)

*Cause:* Unusual sets of credentials that do not match the RPC specifications.

*Example(s):* Backup software such as Legato.

#### ***Ping sweep***

Parameters:

(null)

*Examples:* Network management and monitoring systems when mapping networks.

#### ***Telnet abuse***

Parameters:

port = varies (e.g. 25 | 80 | 100 etc)

*Cause:* Telnet connection attempts to FTP (21), SMTP (25), HTTP (80), POP (110) or IMAP (143).

*Example(s):* Testing to see if a service is running.

#### ***TCP SYN flood***

Parameters:

percentfromintruder = percentage of SYN connects originating from one host

*Cause:* 100 failed TCP connections over a configurable 1-second period.

*Example(s):* Scanning tools, or services that were offline coming back online.

### **Creating a Custom BlackICE Attack Signature [12]**

Custom attack signatures (or 'Intrusions') can be created for all Black ICE agents. The process differs slightly if the agents are standalone (BlackICE Defender) or part of an Enterprise deployment (using an ICEcap console).

The two issues to note are firstly that custom signatures will be overwritten if the agent software is updated, for example by downloading the latest version of Defender or by pushing the latest agent updates from the ICEcap console.

The second issue is that changing the configuration files may have a support implication with your reseller or vendor.

Attack signatures can be written that look for specific patterns in network traffic. The types of patterns include URLs, SMB filenames, FTP filenames, HTTP GET requests, HTTP PUT requests and so on.

The custom attack signature created below will trigger an event when a request to access a "payroll.txt" file over an SMB connection is seen by the IDS agent. Note that this procedure has been tested on agents running on NT machines only.

### Creating a BlackICE Defender 2.5 Custom Attack Signature

- (1) Stop the BlackICE service and close the BlackICE GUI (tray icon)
- (2) Remove the read-only attribute from the 'issuelist.csv' file found in the /program files/Network ICE/BlackICE folder.
- (3) Open the 'issuelist.csv' file and add a row below (for example) issue 2009201 – the ISS Scan issue.
- (4) Enter an unused issue number of 2009202 and give the issue a name (say, **Payroll Access**). Enter a type of 0, an impact of 0, a pk-severity of -1, a di-severity of 4 (up to you), leave roots blank, add a class of Suspicious file and a summary of 'Someone is trying to access the Payroll file' i.e.

**2009202,Payroll Access,0,0,-1,4,,Suspicious file,Someone is trying to access the Payroll file,,**

- (5) Save the 'issuelist.csv' file and make it read-only again.
- (6) Open the 'blackice.ini' file also found under /program files/Network ICE/BlackICE folder and add the following line

**smb.filename.2009202=\*/payroll.txt**

- (7) Restart the BlackICE service and the BlackICE GUI.
- (8) Create a c:\payroll.txt file, map a drive to the NT share \\machinename\c\$ from another machine. Open the payroll.txt file from the remote machine and check the GUI on the target machine for a **Payroll Access** event.

### Creating an Enterprise BlackICE Agent 2.5 Custom Attack Signature

Carry out the following steps on the ICEcap console.

- (1) Stop the ICEcap service, BlackICE service and BlackICE GUI (if installed).

- (2) Edit the both the 'issuelist.csv' files found in the \program files\Network ICE\ICEcap\infobase\issues folder (not read-only) and the 'issuelist.csv' file found under \program files\Network ICE\ICEcap\versions\{agent version}\blackd folder (which is read-only).
- (3) Carry out steps 3, 4 as above on both 'issuelist.csv' files.
- (4) Make the agent 'issuelist.csv' file read-only again.
- (5) Restart the ICEcap, BlackICE services and BlackICE GUI (if installed).
- (6) Login to the web-based ICEcap console with administrative rights. Under the Agent Configuration screen of the target agent add a Custom parameter with a name of **smb.filename.2009202**, a value of **\*/payroll.txt** and a comment of 'Someone is trying to access the Payroll file'.
- (7) Uninstall the remote agents and then reinstall them again from the ICEcap console using the Agent Install mechanism.
- (8) Carry out step 8 as above to test the custom attack signature. Look for the **Payroll Access** event in the BlackICE GUI of the local agent and also check the same event is recorded at the ICEcap console.

A small selection of other custom parameter examples include

```
ftp.filename.issuenumbe=*/texthere
httpget.filename.issuenumbe=*/texthere
email.subject.issuenumbe=*/^Subject: Here
mimepattern.issuenumbe=*.vbs
```

Note: As mentioned, your mileage will vary as any subsequent re-install or update of the agents will overwrite the 'issuelist.csv' file and therefore any custom attack signature you have defined. These custom attacks will need recreating.

#### Appendix – Summary of BlackICE false positives seen on an internal Microsoft network

Event	Parameters	Possible cause
<b>HTTP port probe</b>	port = 80	Attempted web connection to a machine without web services running.
<b>NetBIOS port probe</b>	port = 139	Attempted drive mapping to a machine without NetBIOS services running.
<b>SNMP port probe</b>	port = 161	Enterprise management & monitoring systems.
<b>TCP/UDP port probes</b>	port = varies (e.g. TCP 443 TCP 445)	Monitoring agents failing to connect to busy collection servers. Browsers failing to

		connect to busy HTTPS services. Windows 2000 machines attempting direct host connections to their peers.
<b>TCP/UDP port scans</b>	port = varies (e.g. port1 port2 port3..)	Network backup agents communicating with busy backup servers
<b>MS share dump</b>	(null)	Browsing a share list on a machine
<b>SMB empty password</b>	account = varies share = varies	Connection to non-password protected shares
<b>MS security ID lookup</b>	(null)	Normal MS domain activity. Remote viewing of event logs, viewing user rights in user manager.
<b>SMB login failed</b>	count = varies login = varies victim = varies	Services running as user accounts and password has changed or expired.
<b>MS name lookup</b>	(null)	Normal MS domain activity. MS domain management tools.
<b>SNMP backdoor</b>	community = varies	Network using default SNMP passwords
<b>SNMP discovery broadcast</b>	command = varies	Enterprise management and monitoring system broadcasts.
<b>ICMP subnet mask request</b>	(null)	Network management and monitoring tools.
<b>RPC bad credentials</b>	reason = varies	Network backup agents communicating with backup servers.
<b>Ping sweep</b>	(null)	Network management and monitoring tools.
<b>Telnet abuse</b>	port = varies	Testing of service availability.
<b>TCP SYN flood</b>	percent from intruder = varies	Offline services returns online (e.g. email services).

## References

[1] Database of Intrusions detected by Network ICE  
<http://advice.networkice.com/Advice/Intrusions/default.htm>

[2] SANS reading room: Incident Handling and Forensics  
[http://www.sans.org/infosecFAQ/incident/incident\\_list.htm](http://www.sans.org/infosecFAQ/incident/incident_list.htm)

[3] Firewall-1 Implicit Rules: Security Advisory  
<http://www.codetalker.com/advisories/misc/dil981024.html>

[4] "Code Red" Worm Exploiting Buffer Overflow In IIS Indexing Service DLL  
<http://www.cert.org/advisories/CA-2001-19.html>

[5] Code Red Scanner from eEye Digital Security  
<http://www.eeye.com/html/Research/Tools/codered.html>

[6] A Snapshot of Global Internet Worm Activity  
<http://www.monkey.org/~dugsong/papers/worms/>

[7] Nimda Worm  
<http://www.cert.org/advisories/CA-2001-26.html>

[8] Buffer Overflow Vulnerability in Microsoft IIS 5.0  
<http://www.cert.org/advisories/CA-2001-10.html>

[9] HTTP field with Binary  
<http://advice.networkice.com/advice/Intrusions/2000646/default.htm>

[10] Remote OS detection via TCP/IP Stack Finger Printing  
<http://www.insecure.org/nmap/nmap-fingerprinting-article.html>

[11] Microsoft Windows 2000 TCP/IP Implementation Details  
<http://www.microsoft.com/technet/itsolutions/network/deploy/depovg/tcpip2k.asp>

[12] Discussions with BlackICE support staff.

© SANS Institute 2001, Author retains full rights



# Upcoming SANS Training

[Click Here for a full list of all Upcoming SANS Events by Location](#)

SANS Madrid 2017	Madrid, ES	May 29, 2017 - Jun 03, 2017	Live Event
SANS Atlanta 2017	Atlanta, GAUS	May 30, 2017 - Jun 04, 2017	Live Event
SANS San Francisco Summer 2017	San Francisco, CAUS	Jun 05, 2017 - Jun 10, 2017	Live Event
Security Operations Center Summit & Training	Washington, DCUS	Jun 05, 2017 - Jun 12, 2017	Live Event
SANS Houston 2017	Houston, TXUS	Jun 05, 2017 - Jun 10, 2017	Live Event
SANS Thailand 2017	Bangkok, TH	Jun 12, 2017 - Jun 30, 2017	Live Event
SANS Milan 2017	Milan, IT	Jun 12, 2017 - Jun 17, 2017	Live Event
SANS Charlotte 2017	Charlotte, NCUS	Jun 12, 2017 - Jun 17, 2017	Live Event
SANS Secure Europe 2017	Amsterdam, NL	Jun 12, 2017 - Jun 20, 2017	Live Event
SEC555: SIEM-Tactical Analytics	San Diego, CAUS	Jun 12, 2017 - Jun 17, 2017	Live Event
SANS Rocky Mountain 2017	Denver, COUS	Jun 12, 2017 - Jun 17, 2017	Live Event
SANS Minneapolis 2017	Minneapolis, MNUS	Jun 19, 2017 - Jun 24, 2017	Live Event
DFIR Summit & Training 2017	Austin, TXUS	Jun 22, 2017 - Jun 29, 2017	Live Event
SANS Columbia, MD 2017	Columbia, MDUS	Jun 26, 2017 - Jul 01, 2017	Live Event
SANS Cyber Defence Canberra 2017	Canberra, AU	Jun 26, 2017 - Jul 08, 2017	Live Event
SANS Paris 2017	Paris, FR	Jun 26, 2017 - Jul 01, 2017	Live Event
SEC564:Red Team Ops	San Diego, CAUS	Jun 29, 2017 - Jun 30, 2017	Live Event
SANS London July 2017	London, GB	Jul 03, 2017 - Jul 08, 2017	Live Event
Cyber Defence Japan 2017	Tokyo, JP	Jul 05, 2017 - Jul 15, 2017	Live Event
SANS Los Angeles - Long Beach 2017	Long Beach, CAUS	Jul 10, 2017 - Jul 15, 2017	Live Event
SANS Cyber Defence Singapore 2017	Singapore, SG	Jul 10, 2017 - Jul 15, 2017	Live Event
SANS ICS & Energy-Houston 2017	Houston, TXUS	Jul 10, 2017 - Jul 15, 2017	Live Event
SANS Munich Summer 2017	Munich, DE	Jul 10, 2017 - Jul 15, 2017	Live Event
SANSFIRE 2017	Washington, DCUS	Jul 22, 2017 - Jul 29, 2017	Live Event
Security Awareness Summit & Training 2017	Nashville, TNUS	Jul 31, 2017 - Aug 09, 2017	Live Event
SANS San Antonio 2017	San Antonio, TXUS	Aug 06, 2017 - Aug 11, 2017	Live Event
SANS Prague 2017	Prague, CZ	Aug 07, 2017 - Aug 12, 2017	Live Event
SANS Hyderabad 2017	Hyderabad, IN	Aug 07, 2017 - Aug 12, 2017	Live Event
SANS Boston 2017	Boston, MAUS	Aug 07, 2017 - Aug 12, 2017	Live Event
SANS Salt Lake City 2017	Salt Lake City, UTUS	Aug 14, 2017 - Aug 19, 2017	Live Event
SANS New York City 2017	New York City, NYUS	Aug 14, 2017 - Aug 19, 2017	Live Event
SANS Virginia Beach 2017	Virginia Beach, VAUS	Aug 21, 2017 - Sep 01, 2017	Live Event
SANS Stockholm 2017	OnlineSE	May 29, 2017 - Jun 03, 2017	Live Event
SANS OnDemand	Books & MP3s OnlyUS	Anytime	Self Paced