



Interested in learning more
about cyber security training?

SANS Institute InfoSec Reading Room

This paper is from the SANS Institute Reading Room site. Reposting is not permitted without express written permission.

Immutability Disrupts the Linux Kill Chain

New exploits aimed at Linux systems are able to succeed by achieving root access to the OS. But what if you could lock down the OS and enforce security policies from outside of it? This Spotlight Paper explores the concept of immutability as a way of interdicting the Linux kill chain.

Copyright SANS Institute
Author Retains Full Rights

Immutability Disrupts the Linux Kill Chain

Written by **Hal Pomeranz**

February 2018

Sponsored by:

Immutable Systems

Regardless of the attack vector, successful Linux intrusions share common characteristics. The attacker adds malicious software to the system and executes it. Privilege escalation is the next step, allowing the attacker to modify system files and achieve persistence. Rootkits may then be installed onto the system to hide the attackers' presence.

Targeting these common tactics presents an opportunity to prevent or degrade Linux exploits, even without prior knowledge of the specific exploit used. However, typical Linux security solutions provide incomplete coverage or may provide notification only after a successful attack. Many solutions are difficult to administer, particularly across a large number of systems. And if attackers manage to achieve "superuser" privileges, they can disable or circumvent any security controls in the operating system.

Exploits, Defenses and Limitations

The recent waves of Apache Struts vulnerabilities provide a good example of the early stages of a Linux intrusion. A bug in the Jakarta multipart parser (CVE-2017-5638) allowed attackers to run arbitrary commands with the privileges of the web server process. Typical exploits downloaded executables with **wget** and then executed them. Malicious executables might join the compromised machine to a botnet, or perhaps give the attacker a privilege escalation path to superuser access.



Regardless of the malicious payload, the exploit is taking actions that are abnormal for a Linux server (as shown in Table 1).

No system should be calling out to an external server, pulling down new executables and writing them into the local file system. The executable has to be written to a directory where the web server process has access, which would typically not be one of the normal directories where executables reside. The system should not be running executables from nonstandard locations.

Egress filtering via a host- or network-based firewall could prevent the system from downloading the exploit. But the difficulty of managing firewall policy across a large number of distributed server instances often means that egress filters are either non-existent or incompletely implemented, so that the attackers can achieve their objective.

Properly deployed file-integrity monitoring software could inform the system owner of the new executable, but only *after* the attacker has succeeded. SELinux could prevent the new executable from being written to disk and/or being executed. However, the vast majority of organizations disable SELinux due to difficulty of administration.

Table 1. Exploit Actions, Defenses and Limitations

Exploit Action	Typical Defense	Limitations
Download executable from external site	Egress filtering via firewall	Difficult to manage firewall policies
Add executables to file system	File-integrity monitoring software	Reports <i>after</i> attacker is successful
Execute from writable directories	SELinux and AppArmor	Difficult to administer

Privilege Escalation, Defenses and Limitations

With the ability to run arbitrary code on a Linux system, the attacker's next move is to achieve superuser access. Exploits such as the recent Stack Clash vulnerabilities (e.g., CVE-2017-1000366) coerce a legitimate set-UID executable into executing the attacker's malicious code. Vulnerabilities such as the recent `waitid()` exploit (CVE-2017-5123) write directly to kernel memory to change the effective UID of the attacker's process.

For these exploits to work, abnormal conditions are being created in the operating system (as shown in Table 2).

Stack Clash causes stack and heap memory to collide in the target process—a state that the operating system tries to prevent. The `waitid()` exploit changes the effective UID of the attacker's process in memory without using the typical Linux `setuid()` mechanism. The end result of these and many other privilege escalation exploits is to give the attacker a superuser command shell. Superuser shells should be rare enough that auditing or even selectively preventing them would not be a burden.

In-memory "guard pages" are designed to prevent stack and heap memory regions from overlapping. However, the recent Stack Clash vulnerabilities demonstrated weaknesses in the existing Linux guard page implementation. While these vulnerabilities caused developers to make changes in the Linux kernel, it seems probable that additional vulnerabilities will be found.

Table 2. Privilege Escalation, Defenses and Limitations

Exploit Action	Typical Defense	Limitations
Collide stack and heap memory	In-memory "guard pages"	Weaknesses in implementation
Effective UID change without <code>setuid()</code>	None	N/A
Spawn new superuser process	SELinux and AppArmor	Difficult to administer

SELinux may prevent the attacker’s superuser processes from running. However, as noted earlier, many organizations lack the ability to properly deploy and manage SELinux.

If attackers achieve interactive superuser access, they can disable any security controls in the operating system. This includes reconfiguring or turning off host-based firewalls used for egress filtering, subverting file-integrity monitoring software and disabling SELinux controls. This is a fundamental failing in the Linux security model—nothing in the operating system can block the superuser.

Persistence, Defenses and Limitations

Once attackers have achieved superuser access, it is straightforward for them to modify system startup scripts, scheduled tasks or other configuration files so that their malware will persist across system reboots. The attackers may deploy a rootkit to hide their modifications from the system owner. Modern loadable kernel module (LKM) rootkits such as Phalanx2, KBEAST and Reptile are widely available. (See Table 3.)

Unfortunately, at the point the attacker has achieved superuser privileges, the typical defense against unauthorized configuration file changes—file-integrity monitoring—can be subverted or disabled by the attacker with privileged access. Similarly, the attacker can override attempts by the operating system to prevent the introduction of malicious kernel modules.

Table 3. Defenses Thwarted by Superuser Access

Exploit Action	Typical Defense	Limitations
Modify system config files	File-integrity monitoring	Superuser can disable
Kernel hooking	Policy prevents loading malicious modules	Superuser can disable

Interdiction Through Immutability

Modern, containerized Linux deployments have well-defined behaviors. Large portions of the file system do not change during normal operation. Process UID changes are atypical. Kernel system calls and IDT hooks should not happen. Stack and heap memory should not collide. In other words, large portions of the operating system can be considered “immutable” under normal workloads.

A security policy solution that enforces this immutability blocks the abnormal behaviors of exploits and rootkits—regardless of the specific exploit used—while allowing normal system processes to operate. For example, the following policies would block or degrade the types of exploits covered in this paper:

- Prevent network access to unauthorized sites
- Block unauthorized file system changes
- Prevent unexpected process UID changes
- Monitor superuser processes for suspicious behaviors
- Block system call hooks and IDT hooks used by LKM rootkits
- Prevent collision of process memory regions

Looking Forward

The trick is stopping an attacker with privileged access from subverting these policies. An ideal solution would stand outside the operating system, where it would be invisible and unreachable to an attacker inside the OS.

With increasing numbers of virtualized Linux deployments comes the opportunity to implement security controls outside of the operating system. A hypervisor with security capabilities would be able to interdict memory, file system and network access, applying security policy controls to render critical portions of the operating system immutable. This level of immutability would prevent or seriously degrade typical Linux exploits—regardless of the actual exploit being attempted. Furthermore, the security controls would be invisible to attackers and exploits operating in the Linux OS and could not be subverted from within the OS.

About the Author

Hal Pomeranz is a SANS faculty fellow and the author/instructor for the Securing Linux/Unix (SEC506) course. He is an independent digital forensic investigator who has consulted on cases ranging from intellectual property theft, to employee sabotage, to organized cyber crime and malicious software infrastructures. In the SANS DFIR curriculum, Hal teaches Advanced Digital Forensics, Incident Response, and Threat Hunting (FOR508), Advanced Network Forensics and Analysis (FOR572), Mac Forensics Analysis (FOR518), and Reverse-Engineering Malware: Malware Analysis Tools and Techniques (FOR610).

Sponsor

SANS would like to thank this spotlight paper's sponsor:





Upcoming SANS Training

[Click here to view a list of all SANS Courses](#)

SANS Chicago 2018	Chicago, ILUS	Aug 20, 2018 - Aug 25, 2018	Live Event
Data Breach Summit & Training 2018	New York City, NYUS	Aug 20, 2018 - Aug 27, 2018	Live Event
SANS Prague 2018	Prague, CZ	Aug 20, 2018 - Aug 25, 2018	Live Event
SANS Virginia Beach 2018	Virginia Beach, VAUS	Aug 20, 2018 - Aug 31, 2018	Live Event
SANS San Francisco Summer 2018	San Francisco, CAUS	Aug 26, 2018 - Aug 31, 2018	Live Event
SANS Copenhagen August 2018	Copenhagen, DK	Aug 27, 2018 - Sep 01, 2018	Live Event
SANS SEC504 @ Bangalore 2018	Bangalore, IN	Aug 27, 2018 - Sep 01, 2018	Live Event
SANS Tokyo Autumn 2018	Tokyo, JP	Sep 03, 2018 - Sep 15, 2018	Live Event
SANS Wellington 2018	Wellington, NZ	Sep 03, 2018 - Sep 08, 2018	Live Event
SANS Amsterdam September 2018	Amsterdam, NL	Sep 03, 2018 - Sep 08, 2018	Live Event
SANS Tampa-Clearwater 2018	Tampa, FLUS	Sep 04, 2018 - Sep 09, 2018	Live Event
SANS MGT516 Beta One 2018	Arlington, VAUS	Sep 04, 2018 - Sep 08, 2018	Live Event
Threat Hunting & Incident Response Summit & Training 2018	New Orleans, LAUS	Sep 06, 2018 - Sep 13, 2018	Live Event
SANS Baltimore Fall 2018	Baltimore, MDUS	Sep 08, 2018 - Sep 15, 2018	Live Event
SANS Alaska Summit & Training 2018	Anchorage, AKUS	Sep 10, 2018 - Sep 15, 2018	Live Event
SANS Munich September 2018	Munich, DE	Sep 16, 2018 - Sep 22, 2018	Live Event
SANS London September 2018	London, GB	Sep 17, 2018 - Sep 22, 2018	Live Event
SANS Network Security 2018	Las Vegas, NVUS	Sep 23, 2018 - Sep 30, 2018	Live Event
SANS DFIR Prague Summit & Training 2018	Prague, CZ	Oct 01, 2018 - Oct 07, 2018	Live Event
Oil & Gas Cybersecurity Summit & Training 2018	Houston, TXUS	Oct 01, 2018 - Oct 06, 2018	Live Event
SANS Amsterdam October 2018	Amsterdam, NL	Oct 08, 2018 - Oct 13, 2018	Live Event
SANS Brussels October 2018	Brussels, BE	Oct 08, 2018 - Oct 13, 2018	Live Event
SANS Northern VA Fall- Tysons 2018	Tysons, VAUS	Oct 13, 2018 - Oct 20, 2018	Live Event
SANS Riyadh October 2018	Riyadh, SA	Oct 13, 2018 - Oct 18, 2018	Live Event
SANS London October 2018	London, GB	Oct 15, 2018 - Oct 20, 2018	Live Event
SANS October Singapore 2018	Singapore, SG	Oct 15, 2018 - Oct 27, 2018	Live Event
SANS Seattle Fall 2018	Seattle, WAUS	Oct 15, 2018 - Oct 20, 2018	Live Event
SANS Denver 2018	Denver, COUS	Oct 15, 2018 - Oct 20, 2018	Live Event
Secure DevOps Summit & Training 2018	Denver, COUS	Oct 22, 2018 - Oct 29, 2018	Live Event
SANS Houston 2018	Houston, TXUS	Oct 29, 2018 - Nov 03, 2018	Live Event
SANS Gulf Region 2018	Dubai, AE	Nov 03, 2018 - Nov 15, 2018	Live Event
SANS Dallas Fall 2018	Dallas, TXUS	Nov 05, 2018 - Nov 10, 2018	Live Event
SANS Krakow 2018	OnlinePL	Aug 20, 2018 - Aug 25, 2018	Live Event
SANS OnDemand	Books & MP3s OnlyUS	Anytime	Self Paced