



Interested in learning
more about security?

SANS Institute InfoSec Reading Room

This paper is from the SANS Institute Reading Room site. Reposting is not permitted without express written permission.

Your Greatest Strength can become your Greatest Weakness: Simple Network Management Protocol Vulnera

According to the recent press coverage, multiple vulnerabilities have been discovered in the widely used Simple Network Management Protocol (SNMP). This paper will discuss some of the major vulnerabilities discovered in SNMP and their potential impact as well as some of the major vendors affected by these vulnerabilities and possible solutions and alternatives that can be implemented to protect systems from these vulnerabilities.

Copyright SANS Institute
Author Retains Full Rights



AD

Your Greatest Strength can become your Greatest Weakness: Simple Network Management Protocol Vulnerabilities

Summary

According to the recent press coverage, multiple vulnerabilities have been discovered in the widely used Simple Network Management Protocol (SNMP). This paper will discuss some of the major vulnerabilities discovered in SNMP and their potential impact as well as some of the major vendors affected by these vulnerabilities and possible solutions and alternatives that can be implemented to protect systems from these vulnerabilities.

Background

Simple Network Management Protocol (SNMP) was developed in the late 1980's by the Internet Engineering Task Force to provide a standard network management protocol to manage network devices. As its name implies, simplicity was the focus of this protocol as it was being developed. SNMP's ultimate goal was interoperability so it could be widely used across most all platforms and devices. Its developers accomplished this goal, as demonstrated by its use in almost every major networking product on the market. SNMP's simplicity was designed to minimize the overhead needed to run such a protocol and keep the complexity of network management to a minimum.

SNMP is a request-reply protocol that runs over UDP (User Datagram Protocol) on ports, paths into and out of a computer or network device, 161 and 162. The protocol operates between a management station, acting as the control center for network monitoring, and an agent, the network device that is being managed by the management station. The management station will send out requests to the agent for data on configuration, operational status, and performance statistics. SNMP uses five control primitives or commands to monitor a network device: GetRequest/Set Request, GetResponse, GetNextRequest, and Trap. GetRequest, GetNextRequest, and SetRequest initiate data flows from the management station to an agent on the network. The agent will respond with GetResponse to any of these primitives. The agent, however, can also send an uninitiated primitive to the management station using the

Trap primitive to alert the station of an unusual event that may need attention.

It is important to remember that SNMP agents cannot perform any analysis on the information they collect, they can only send out a Trap primitive and alert the management station that they have information to give it. The management station will then aggregate the data it receives back from its agents. The burden of actually analyzing and drawing conclusions from the information provided to the management station is the responsibility of the administrator responsible for the management station. In some cases, multiple management stations can be run on the same network and their aggregate data can be sent to a central location for analysis.

There are three versions of SNMP in use today - SNMPv1, SNMPv2, and SNMPv3. The second version of SNMP introduced new management capabilities including: manager-to-manager communication to allow multiple station managers to be running on the same network, enhanced security, and improved efficiency and performance. The testing that was carried out by Oulu University Secure Programming Group (OUSPG) that revealed the vulnerabilities in the protocol was only performed on SNMPv1. It is believed that similar vulnerabilities may exist in the later versions of SNMP.

Vulnerabilities

Recently, a lot of press has been given to the vulnerabilities the Oulu University Secure Programming Group (OUSPG) has found in SNMPv1 implementations. But long before these vulnerabilities were discovered another vulnerability existed that can have just as much impact on an organization's systems as the two new vulnerabilities brought to light by OUSPG. According to Deborah Radcliff, "SNMP uses the community name 'default'... if this community name isn't changed, attackers can slip right in and control SNMP to map your network, change routes of packets and all kinds of evil things." (www.computerworld.com - "Cover you SNMP") She goes on to say that attackers could even change IP addresses and bring down critical interfaces. This vulnerability has been public for over two years, but it still warrants attention because of the amount of network

exposure that could result if this vulnerability were exploited.

A community string or community name is a weak form of authentication used by SNMP agents and management stations. An agent can be configured as read-only, read-write, or no access based on the community string used in the packets sent to an agent from the management station. Changing the community string from "default" to another identifier will help to mitigate the risks presented by this vulnerability. However, the community string is not encrypted in the packets that are sent to the agents, instead the community string is sent in plain-text, leaving it open to possible packet sniffing by would-be attackers. Even with the community string changed, this method of authentication should not be relied upon to secure the protocol. This method should be used in conjunction with other security measures to thoroughly mitigate these risks.

The potential impacts of this vulnerability are large and far-reaching. Once an attacker has access to the SNMP, they can not only see all the hardware that is running on the system, but also the information that is being exchanged through the network. The attacker can also see UDP services that could reveal the other active network services that an organization is running on their network. This vulnerability also opens systems up to additional vulnerabilities. If an attacker can map the network they can target critical services and devices running on the system for other attacks. Critical machines such as Domain Name Servers and Mail Servers can easily be found if an attacker is able to map the network. These two machines are a favorite of attackers who want to gain access to password files. Once an attacker gains access to a password file the network can be opened up further.

The most recent vulnerabilities in SNMP that were discovered by OUSPG may also have heavy impacts on systems. According to CERT Advisory CA-2002-03 the two new vulnerabilities discovered are:

VU#107186-Multiple vulnerabilities in SNMPv1 trap handling:

"SNMP trap messages are sent from agents to managers. A trap message may indicate a warning or error condition or otherwise notify the manager about the agent's state. SNMP managers must properly decode trap messages and process the resulting data. In testing, OUSPG found multiple vulnerabilities in the way many SNMP managers decode and process SNMP trap messages." (www.cert.org - CERT Advisory CA-2002-03)

VU#854306-Multiple vulnerabilities in SNMPv1 request handling:

"SNMP request messages are sent from managers to agents. Request messages might be issued to obtain information from an agent or to instruct the agent to configure the host device. SNMP agents must properly decode request messages and process the resulting data. In testing, OUSPG found multiple vulnerabilities in the way many SNMP agents decode and process SNMP request messages." (www.cert.org - CERT Advisory CA-2002-03)

OUSPG initiated a two-pronged test that would send thousands of malformed SNMPv1 packets to an agent. The first part of the test focused on the get, getnext, and set operations of SNMP, while the second part of the test generated traps. SNMP products by all vendors tested failed these tests, exposing the vulnerabilities in SNMP.

These vulnerabilities are caused by differences in the ways vendors' devices receive, decode, and process SNMP service requests. If SNMP packets are malformed, errors in processing can occur either at the agent or at the management station. Depending on the device or vendor, these processing errors can cause a device to reboot or crash.

The potential impacts from these vulnerabilities can range from denial-of-service conditions, format string

vulnerabilities, and buffer overflows. According to CERT, attackers may even be able to gain unauthorized access to systems. The impact of these vulnerabilities will not only affect a network, but could have far-reaching business impacts on a company's bottom line. For a business that has built their business model around e-commerce, a denial-of-service attack that brings down their site could be extremely costly. Likewise, if an attacker gained unauthorized access to a network, passwords could be harvested, possibly giving the attacker access to extremely confidential information such as customer credit card numbers or employee benefit information. The potential business impacts of an attack like this could also cost a company dearly either in the form of lost revenue or degradation of reputation.

One thing that makes these vulnerabilities so critical is the fact that the use of SNMP is so ubiquitous in the world of network management. With so many networks at risk because of these vulnerabilities, it is necessary to address these issues quickly. The fact that these vulnerabilities have been made public is helpful to administrators trying to keep their networks secure; on the other hand, it also makes everyone a potential target because would-be attackers are now aware of the vulnerabilities as well. Patching these vulnerabilities is not an option if one wants their network to be secure, either patch the devices or shut off the service.

Major Vendors Affected

As it turns out, one of SNMP's early features that was heralded as one of its greatest strengths, may now turn out to be one of its greatest weaknesses. The simplicity of this protocol has allowed for widespread use and interoperability across systems, unfortunately, this now also leaves most networks vulnerable and has most vendors clamoring for fixes. SNMP usage is not limited to what most people think of as typical network devices, like routers. SNMP runs on operating systems, cable and DSL modems, image scanners and digital cameras, printers, copiers and fax machines, network management devices, and many other devices not typically thought of as core network devices. Cisco, Sun, and Microsoft are just a few of the

major vendors whose products are affected by these newly discovered vulnerabilities.

Cisco, a major producer of network routers and hubs, has a number of devices that are susceptible to these vulnerabilities if they are exploited. Typically, if exploited, these vulnerabilities would cause the Cisco device to crash and reboot. An attacker could carry out a denial of service attack by flooding a network with malformed SNMP messages that cause the network devices to crash once they try to process the SNMP requests. Cisco has attempted to generate fixes for all of its products that are susceptible to these vulnerabilities; however not all of their products have fixes yet. Cisco recommends that their customers go to the Cisco website to check for fixes and upgrade the release of their hardware to patch these vulnerabilities, if patches exist. (www.Cisco.com)

Sun Microsystems, a major producer of core network devices and servers, is another major vendor that has been affected by these recent vulnerabilities. According to Sun's security bulletin, Sun's Solstice Enterprise Master Agent - snmpdx, is vulnerable to a buffer overflow that, if exploited, would allow root access to the affected system. Root access to a network would give a potential attacker most of the information they need to take full advantage of a network and the information contained within it. Like Cisco, Sun has quickly found ways to patch their systems and have made these patches available on their website. (www.sun.com)

Even Microsoft products have been affected by these vulnerabilities. Like Cisco and Sun, exploiting these vulnerabilities will cause a buffer overrun, which could result in a denial of service. Both Microsoft Windows 2000 and the Windows XP operating systems are susceptible to these exploits, as they provide for SNMP implementation. One positive in this case, however, is that SNMP implementation is not part of the default installation for either operating system. This helps to minimize the risk that users are running systems with vulnerabilities they don't know they are susceptible to. Similar to the other two vendors we have looked at, Microsoft is also developing patches for their systems to eliminate the vulnerability. The Microsoft website has full details on patches that have

and are being developed. The first step in patching the vulnerabilities affecting either Windows version is to check to see if the SNMP service has been enabled. If the SNMP service is not installed on the operating system, the operating system is not vulnerable, although other devices running on the network may still be vulnerable.

Unilaterally, vendors and watch groups alike are recommending network administrators disable all of their SNMP services as a near-term fix until all of the vulnerabilities in the system can be adequately patched. One of the difficulties faced by network administrators now is the widespread need for patches throughout their networks. As Josh Turiel, the network services manager at Holyoke insurance company, said, "The more intricate your network is, the more exposed you are." (www.computerworld.com - "SNMP Devices Open to Attacks") Again, the interoperability of this protocol has made almost everything from routers to operating systems vulnerable to these threats, making the job of patching a system quite a headache for administrators. Literally every layer of the network will need to be thoroughly checked for potential vulnerabilities. Once discovered, these holes will need to be patched if fixes are available. If fixes aren't available for some of the products on the network running SNMP, an interim workaround solution will need to be developed until everything can be patched.

Solutions and Alternatives

While these vulnerabilities do pose serious risks to networks operating SNMP, the risks they expose an organization to can be mitigated in a number of ways. The obvious first step in this process would be to disable all SNMP services. Disabling SNMP services will eliminate any risks associated with these vulnerabilities, as SNMP has to be running for the vulnerabilities to be exploited. Still, SNMP provides a valuable service to network administrators so most businesses will consider this step only a short-term fix. Disabling SNMP services will allow system administrators time to check the devices running on their networks so that vendors can be contacted regarding fixes and patches.

Patches and fixes are another avenue that can be used to mitigate the risk associated with these vulnerabilities. While patches and fixes may eliminate the vulnerability in a certain device, they can only mitigate the risk to a network if the patches are installed! So, the identification of vulnerable devices and the subsequent installation of patches on affected devices will help to mitigate these risks.

In addition to patching vulnerable devices, ingress and egress filtering can be performed on the network. Ingress filtering filters network traffic as it enters the network and egress filtering filters network traffic as it leaves the network. Only those devices that have a business need to accept inbound traffic should do so. Likewise, only devices that have a business need to initiate outbound traffic should do so. Extraneous inbound or outbound communication could indicate an attack is being initiated on the network. Monitoring outbound traffic is a powerful diagnostic to prevent your network from being used to attack another unsuspecting networks with similar vulnerabilities. The presence of unusual amounts of outbound traffic could indicate the network is being used in the attack of another network. If unusual outbound traffic is caught in time, disabling the system could help prevent or cut-short another attack on a similar network. Ports 161 and 162 both provide SNMP services; these ports should be filtered and watched closely.

Another type of filtering can be performed to help mitigate risk as well. SNMP packets can be filtered to determine what devices are sending them. Agents should only accept traffic that comes from known management stations and management stations should only accept traffic that is responding to a valid request or a trap sent from a known agent. For example, SNMP traffic from a management stations should come from inside the network. If the filter detects that this traffic is coming from an external source it should alert the system. This security measure will help to ensure that an attacker is not spoofing SNMP traffic to gain access or shut down the network.

Another way to keep an eye on a network is to log traffic coming into, flowing through, and exiting the network. Logging is by no means a security strategy specific to

these SNMP vulnerabilities; it is a generally accepted best practice to help secure systems. Traffic logging can help network administrators notice unusual traffic patterns that may indicate an attack. Logging will not prevent the attacks, but it can help network administrators gain valuable information regarding who is attacking them and what methods they are using.

As mentioned above, a specific fix to address the community string vulnerability is relatively simple to implement, change the default community strings. This does not, however, guarantee that an attacker will not gain access to a network using this vulnerability. The community string can still be cracked if an attacker intercepts a packet with the community string in it. This will, however, make the attacker work harder and longer to crack the community string, possibly giving a security administrator enough time to detect the potential attack and react to it.

Conclusion

Vendors and watch groups alike have done a great job of educating the public on these vulnerabilities and working to find solutions and patches to these problems so that SNMP can be implemented and used without fear of repercussions. Still, all the patches and public knowledge cannot take the place of an organized, well secured network. The burden of eliminating vulnerability ultimately falls squarely on the shoulders of network administrators and security administrators who need to be proactive in installing patches and vigilant about monitoring their systems.

Securing systems goes way beyond installing the appropriate patches to fix system vulnerabilities, although this is a good place to start. A combination of techniques should be used to thoroughly secure systems. The use of firewalls, vulnerability scanners, virus protection and a combination of host based intrusion detection and network intrusion detection systems will help to mitigate the risk of a system compromise that could have dangerous impacts on a business. The introduction of these new SNMP vulnerabilities proves that the security landscape of a network is always changing. Flexibility is a crucial mindset for a network administrator to possess when it

comes to security. Just because vulnerabilities have been found in the SNMP protocol, does not mean it needs to be abandoned as a means of network management. Appropriate precautions should be taken to mitigate the risks it presents. As with most things that are valuable to a company, a certain amount of risk must be accepted to reap the benefits of the returns it affords the business.

SNMP is a valuable protocol that enables network administrators to effectively manage their network. SNMP strengths lie in its low overhead and high interoperability among network devices, operating systems, and other peripherals. The risks and impacts of these vulnerabilities have been augmented by the depth and breadth of SNMP's use in the market, an affect of its interoperability. I guess it is true what they say; your greatest strength can become your greatest weakness.

© SANS Institute 2003, Author retains full rights.

Works Cited:

CERT Advisory CA-2002-03. "Multiple Vulnerabilities in Many Implementations of Simple Networking Management Protocol."

<http://www.cert.org/advisories/CA-2002-03.html>

Cisco Security Advisory: "Malformed SNMP Message-Handling Vulnerabilities"

<http://www.cisco.com/warp/public/707/cisco-malformed-snmp-msgs-pub.shtml>

Connected: An Internet Encyclopedia. "SNMP Protocol Overview" <http://freesoft.org/CIE/Topics/108.htm>

Carnegie Mellon University. "Simple Network Management Protocol"

http://www.sei.cmu.edu/str/descriptions/snmp_body.html

Dean, Joshua. "Newly Identified Security Gaps Threaten Internet."

<http://www.govexec.com/dailyfed/0202/021502j1.htm>

Microsoft Security Bulletin. "MS02-006"

<http://www.microsoft.com/technet/security/bulletin/NS02-006.asp?frame=true>

Radcliff, Deborah. "Cover Your SNMP."

<http://www.computerworld.com/cwi/Printer Friendly Version/0,1212,NAV47 STO41144-,00.html>

SNMP Research International, INC. "SNMP Research: CERT/OUSPG Update" <http://www.snmp.com/cert.html>

Sun Security Bulletins. "Article 215"

<http://sunsolve.sun.com/pub-cgi/retrieve.pl?doctype=col&doc=secbull/215&type=0&nav=sec.sba>

Vijayan, Jaikumar. "SNMP Devices Open to Attacks."

<http://www.computerworld.com/cwi/Printer Friendly version/0,1212,KEY73 STO68438-,00.html>



Upcoming SANS Training

[Click Here for a full list of all Upcoming SANS Events by Location](#)

SANS Cyber Defence Canberra 2017	Canberra, AU	Jun 26, 2017 - Jul 08, 2017	Live Event
SANS Columbia, MD 2017	Columbia, MDUS	Jun 26, 2017 - Jul 01, 2017	Live Event
SEC564:Red Team Ops	San Diego, CAUS	Jun 29, 2017 - Jun 30, 2017	Live Event
SANS London July 2017	London, GB	Jul 03, 2017 - Jul 08, 2017	Live Event
Cyber Defence Japan 2017	Tokyo, JP	Jul 05, 2017 - Jul 15, 2017	Live Event
SANS ICS & Energy-Houston 2017	Houston, TXUS	Jul 10, 2017 - Jul 15, 2017	Live Event
SANS Cyber Defence Singapore 2017	Singapore, SG	Jul 10, 2017 - Jul 15, 2017	Live Event
SANS Los Angeles - Long Beach 2017	Long Beach, CAUS	Jul 10, 2017 - Jul 15, 2017	Live Event
SANS Munich Summer 2017	Munich, DE	Jul 10, 2017 - Jul 15, 2017	Live Event
SANSFIRE 2017	Washington, DCUS	Jul 22, 2017 - Jul 29, 2017	Live Event
Security Awareness Summit & Training 2017	Nashville, TNUS	Jul 31, 2017 - Aug 09, 2017	Live Event
SANS San Antonio 2017	San Antonio, TXUS	Aug 06, 2017 - Aug 11, 2017	Live Event
SANS Hyderabad 2017	Hyderabad, IN	Aug 07, 2017 - Aug 12, 2017	Live Event
SANS Boston 2017	Boston, MAUS	Aug 07, 2017 - Aug 12, 2017	Live Event
SANS Prague 2017	Prague, CZ	Aug 07, 2017 - Aug 12, 2017	Live Event
SANS Salt Lake City 2017	Salt Lake City, UTUS	Aug 14, 2017 - Aug 19, 2017	Live Event
SANS New York City 2017	New York City, NYUS	Aug 14, 2017 - Aug 19, 2017	Live Event
SANS Chicago 2017	Chicago, ILUS	Aug 21, 2017 - Aug 26, 2017	Live Event
SANS Adelaide 2017	Adelaide, AU	Aug 21, 2017 - Aug 26, 2017	Live Event
SANS Virginia Beach 2017	Virginia Beach, VAUS	Aug 21, 2017 - Sep 01, 2017	Live Event
SANS San Francisco Fall 2017	San Francisco, CAUS	Sep 05, 2017 - Sep 10, 2017	Live Event
SANS Tampa - Clearwater 2017	Clearwater, FLUS	Sep 05, 2017 - Sep 10, 2017	Live Event
SANS Network Security 2017	Las Vegas, NVUS	Sep 10, 2017 - Sep 17, 2017	Live Event
SANS Dublin 2017	Dublin, IE	Sep 11, 2017 - Sep 16, 2017	Live Event
SANS Paris 2017	OnlineFR	Jun 26, 2017 - Jul 01, 2017	Live Event
SANS OnDemand	Books & MP3s OnlyUS	Anytime	Self Paced