



Interested in learning
more about security?

SANS Institute InfoSec Reading Room

This paper is from the SANS Institute Reading Room site. Reposting is not permitted without express written permission.

Network Monitoring with Nagios

Nagios is a network-monitoring tool that allows administrators the ability to examine computers, routers, printers, and services. Many organizations opt for pricey commercial solutions such as HP-OpenView. Nagios is an excellent solution for those companies looking for a product that is inexpensive (free) and under constant development due to open source availability. Currently there is not a stable release for Nagios, only an alpha version available for download. The reason for the delayed release is not as much appli...

Copyright SANS Institute
Author Retains Full Rights

AD



EMM Strategy on the right track?
Know your security risks.

[TAKE THE ASSESSMENT](#)

NETWORK MONITORING WITH NAGIOS

Scott V. Seglie

September 25, 2001

Introduction to Nagios

Nagios is a network-monitoring tool that allows administrators the ability to examine computers, routers, printers, and services. Many organizations opt for pricey commercial solutions such as HP-OpenView. Nagios is an excellent solution for those companies looking for a product that is inexpensive (free) and under constant development due to open source availability. Currently there is not a stable release for Nagios, only an alpha version available for download. The reason for the delayed release is not as much application issues as it is lack of documentation. An Admin Kit with additional documentation, videos, etc will be available for purchase in January 2002.

Some of the many features of Nagios include:

- Monitoring of network services (SMTP, POP3, HTTP, NNTP, PING, etc.)
- Monitoring of host resources (processor load, disk usage, etc.)
- Simple plug-in design that allows users to easily develop their own service checks
- Parallel service checks
- Ability to define network host hierarchy using "parent" hosts, allowing detection of and distinction between hosts that are down and those that are unreachable
- Contact notifications when service or host problems occur and get resolved (via email, pager, or user-defined method)
- Ability to define event handlers to be run during service or host events for proactive problem resolution
- Automatic log file rotation
- Support for implementing redundant monitoring hosts
- Optional web interface for viewing current network status, notification and problem history, log files, etc.

Nagios was developed and is maintained by Ethan Galstad. The original project was known by the name of Netsaint. The last official release of Netsaint was 0.0.7. Due to legal issues, the name "Netsaint" is no longer used. Further development of this project is now known as Nagios.

The major advantage of Nagios is the same as the major disadvantage: extreme flexibility. This is obviously great for administrators that require complete control and flexibility of the application. It also means days of reading, testing, and tweaking. Nagios is not a simple click-and-go installation. There are numerous packages that are required for Nagios to run properly. My advice: Block a few days off on your schedule, join the nagios-users mailing list, read the online documentation, read the man pages, read the install pages, and then read everything again.

Step-By-Step Installation

Nagios was originally written for the Linux operating system, but ports are now available for many other platforms. This document is intended to detail the Nagios installation process on a default install of Red Hat 7.0 workstation.

Nagios requires many other programs to operate effectively. A major piece of Nagios are the CGIs. CGIs are part of the Nagios installation and are not required for the program to run, although significantly add to the overall functionality of the program. Apache and Thomas Boutell's GD Library must be installed to utilize the CGIs and other features of the application.

Install and Configure Apache

Apache is used as a front-end web interface to Nagios and adds additional security. (note: Apache is recommended, but other web servers will work.)

Install the Apache RPM located on the Red Hat 7.0 CD under /RedHat/RPMS/
Once install is complete, modify the httpd.conf file located at
/etc/httpd/conf/httpd.conf by removing the comment “#” before the “ServerName localhost” line
Save the file and exit
Open a shell type: “/etc/rc.d/init.d/httpd restart” to restart the Apache daemon
Test the Apache installation by opening Netscape and typing "localhost" in the address. If the default Apache page comes up, the installation was successful.

Install Thomas Boutell's GD Library (version 1.6.3 or higher is required)

Thomas Boutell's GD Library – this supports the most important *.cgi; the status.cgi, which shows the current status of all hosts and services being monitored.

Thomas Boutell's GD Library requires the following packages:

- libpng (already installed in default Red Hat 7.0)
- zlib (already installed in default Red Hat 7.0)
- jpeg-6b or later (this package can be found at <http://rpmfind.net>)

Download the GD library package at: <http://www.boutell.com/gd/>
gunzip [gd_library_package_name].tar.gz
tar -xf [gd_library_package_name].tar
cd [gd_library_package_name]
make
make install
note: if the error: “/usr/local/include/dg.h: No such file or directory” occurs, simply type the command “mkdir /usr/local/include” in a shell, then re-do the “make install”

Install Nagios

Download Nagios from <https://www.nagios.org> (the alpha version is available at: <http://www.nagios.org/download/>)

```
gunzip [nagios_package].tar.gz
tar -xf [nagios_package].tar
mkdir /usr/local/nagios
adduser nagios
passwd nagios
./configure
make all
make install
make install-init
make install-config
cd /usr/local/nagios
mkdir etc
mkdir libexec
```

Of note, Nagios runs as a specific user, “nagios,” which adds to the overall security of the application and is a basic security precaution. Everything, including your Nagios configuration files should be treated on a 'need to know' only basis.

Install the Plug-ins

Nagios uses plug-ins to perform actual service checks on the computers, routers, printers, and services. This is a very flexible approach that allows new plug-ins to be created by the user for more granular checks. Since this project is open source, many of the personalized plug-ins are available to the public.

These plug-ins use additional tools that should also be installed. The additional files are: snmpget, qstat, and fping. Make sure to install these before you go on to the Nagios plug-ins install. Searches at <https://rpmfind.net> will allow for download. Documentation below describes the plug-in install steps.

Download the *Netsaint* plug-ins.tar.gz from <http://netsaintplug.sourceforge.net>. The Netsaint plug-ins are compatible with Nagios, but continue to check the Nagios website for the first release of plug-ins for the new project.

```
gunzip [netsaint-plug-ins].tar.gz
tar -xf [netsaint-plug-ins].tar
cd [netsaint-plug-ins]
#autoconf
#autoheader
#automake
./configure --prefix=/usr/local/nagios --with-netsaint-user=nagios --with-netsaint-
group=nagios --with-cgiurl=/cgi-bin/nagios
make all
make install
```

note: make sure hosts.cfg contains the correct paths to the new plug-ins

Setting Up and Configuring the Web Server

Go to the `/etc/httpd/conf` directory and open the `httpd.conf` file. There are two modifications necessary in this file.

Before the “Alias” that is already there, type:

```
Alias /nagios/ "/usr/local/nagios/share/"
```

(note: the “quote” marks should be included)

Before the `ScriptAlias` type:

```
ScriptAlias /cgi-bin/nagios/ /usr/local/nagios/sbin/
```

Important! The `ScriptAlias` entry for the CGIs must precede the standard `ScriptAlias` directive already present in the configuration file. If this configuration is not followed, use of the CGIs may not be available.

Once you've finished editing the Apache configuration file, you'll need to restart the web server with the following command:

```
/etc/rc.d/init.d/httpd restart
```

Verify the Changes

It is important to make sure the changes to Apache work correctly. If `http://yourmachine/nagios/` brings up the web interface, then the changes thus far are complete. None of the links will work at this step since Nagios is not running. Also, the functionality of the CGIs and other features have not yet been configured.

Configuring the Web Server for Authentication

The first step to configuring the web server for authentication is to make sure the `access.conf` file located at `/etc/httpd/conf` contains an “AuthOverride AuthConfig” statement in it for the Nagios `cgi-bin` directory. By default, the statement does not exist and it is necessary to add the following text to the `access.conf` file.

```
<Directory /usr/local/nagios/sbin>  
AllowOverride AuthConfig  
order allow,deny  
allow from all  
Options ExecCGI  
</Directory>
```

It is not required to authorize a user to the HTML pages, but the option is available. To do this, add the statement below to the `access.conf` file as well.

```
AllowOverride AuthConfig  
order allow,deny  
allow from all
```

The second step is to create a file named `.htaccess` in the root your CGI directory (and optionally also you HTML directory) for Nagios. This file(s) should be located in the `/usr/local/nagios/sbin` directory and the `/usr/local/nagios/share` directory, respectively. The file(s) should have contain the following text

```
AuthName "Nagios Access"  
AuthType Basic  
AuthUserFile /usr/local/nagios/etc/htpasswd.users  
require valid-user
```

It is necessary to create the `AuthUserFile` and create the Nagiosadmin account by entering the following command:

```
htpasswd -c /usr/local/nagios/etc/htpasswd.users Nagiosadmin
```

Next, make sure that the CGIs are configured to use the authentication and authorization functionality in determining what information and/or commands users have access to. This is done by setting the `use_authentication` variable in the CGI configuration file (`cgi.cfg` in the `/etc` directory of the Nagios installation) to a non-zero value. The `use_authentication` variable should be set to equal 1. (`use_authentication=1`)

There are many options in the `cgi.conf` file that allow more privileges. To gain additional access, remove the comments (“#”) from the following variables:

```
authorized_for_system_information  
authorized_for_system_commands  
authorized_for_configuration_information  
authorized_for_all_hosts  
authorized_for_all_host_commands  
authorized_for_all_services  
authorized_for_all_service_commands
```

Modifying the .cfg Files

There are several configuration files that Nagios utilizes when monitoring the network. Nagios configuration files are located in the `/usr/local/etc/nagios` directory. Fortunately, these files are highly configurable. Unfortunately, each administrator will require different services, computers, and processes be monitored on the network. The individual configuration of each of these files is not in scope of this document. Information on these files is provided below. Further information on the configuration of these files may be found on the Nagios website and in the manual pages.

Main Configuration File

The default installation places the main configuration file in the `/usr/local/nagios/etc` directory. The Nagios processes and the CGIs both read the `nagios.cfg` file. A sample main configuration file is automatically generated when the `make install-config` script is run during install.

Resource Files

Resource files are used to store user-defined settings. These files also contain other information such as database connection settings depending on how Nagios was configured. The main purpose of the resource files is to store sensitive configuration information.

Object Configuration Files

Object configuration files are used to define the hosts, services, hostgroups, contacts, contactgroups, comments, etc. relative to the network Nagios is monitoring. These files define what is to be monitored and how to monitor them.

CGI Configuration File

The CGI configuration file contains directives that affect the operation of the CGIs. A sample configuration file is generated when the *make install-config* script is run.

Extended Information Configuration Files

These files are used to define additional information for hosts and services that should be used by the CGIs. The extended information files allow the user to define icons and information to draw coordinates.

Verifying the Configuration

With all of the necessary modifications, it is necessary to run a test to verify the existing setup. This step is extremely helpful when troubleshooting Nagios because this check will produce error messages with additional information on where the error occurred.

Nagios automatically runs a “pre-check” before monitoring begins, but the check can also be initiated manually by using the following command:

```
usr/local/nagios/bin/nagios -v /usr/local/nagios/etc/nagios.cfg
```

Starting Nagios

There are four ways to initiate Nagios:

Manually, as a foreground process (useful for initial testing and debugging)
Nagios has the option to enable debugging during the initial configure script.
Running Nagios as a foreground process in a shell prompt will allow simplified monitoring and notification processes.

```
/usr/local/nagios/bin/nagios /usr/local/nagios/etc/nagios.cfg
```

Manually, as a background process

To run Nagios as a background process, invoke it with an ampersand.

```
/usr/local/nagios/bin/nagios /usr/local/nagios/etc/nagios.cfg &
```

Manually, as a daemon

The `-d` switch is required to run Nagios in daemon mode.

```
/usr/local/nagios/bin/nagios -d /usr/local/nagios/etc/nagios.cfg
```

Automatically at system boot

After Nagios has been tested and seems reasonable stable, enable Nagios to start automatically during boot. A startup script will need to be placed in the `/etc/rc.d/init.d/` directory. A link to the script will also be required in the runlevel that Nagios should start in. A sample script is created (`daemon-init`) during the `make install-init` command.

Nagios is still in the alpha release stages, but has been in open source development under the previous name “Netsaint” for some time. Nagios is an excellent solution for any company requiring a comprehensive network monitoring utility. Prerequisites: time and patience.

© SANS Institute 2001, Author retains full rights

Sources

[1] Galstad, Ethan. "Nagios." 1999-2001. URL:
<http://www.nagios.org>

[2] Galstad, Ethan. 1999-2001. Program manual pages.

[3] Galstad, Ethan. "Netsaint." 1999-2001. URL:
<http://www.netsaint.org>

[4] Bar, Moshe. "How to Monitor Networks with Linux." July 28, 1999. URL:
<http://www.byte.com/documents/s=94/byt19990728s0008/index.htm>

[5] Unknown author. "Netsaint-a network monitor." September 10, 2001. URL:
<http://www.freebsdidiary.org/netsaint.php>

[6] Geocrawler. "Netsaint-users – 2001." URL:
<http://www.geocrawler.com/archives/3/1108/2001/>

Additional Sources

The Apache Project URL: <http://httpd.apache.org/>

GD Graphics Library URL: <http://www.boutell.com/gd/>

Freshmeat URL: <http://freshmeat.net/projects/netsaint/>

SourceForge URL: <http://sourceforge.net/projects/nagios/>

RPM repository for Rpmfind.net URL: <http://rpmfind.net/>

© SANS Institute 2001. Author retains full rights.



Upcoming SANS Training

[Click Here for a full list of all Upcoming SANS Events by Location](#)

SANS San Francisco Winter 2017	San Francisco, CAUS	Nov 27, 2017 - Dec 02, 2017	Live Event
SIEM & Tactical Analytics Summit & Training	Scottsdale, AZUS	Nov 28, 2017 - Dec 05, 2017	Live Event
SANS Khobar 2017	Khobar, SA	Dec 02, 2017 - Dec 07, 2017	Live Event
SANS Munich December 2017	Munich, DE	Dec 04, 2017 - Dec 09, 2017	Live Event
European Security Awareness Summit & Training 2017	London, GB	Dec 04, 2017 - Dec 07, 2017	Live Event
SANS Austin Winter 2017	Austin, TXUS	Dec 04, 2017 - Dec 09, 2017	Live Event
SANS Frankfurt 2017	Frankfurt, DE	Dec 11, 2017 - Dec 16, 2017	Live Event
SANS Bangalore 2017	Bangalore, IN	Dec 11, 2017 - Dec 16, 2017	Live Event
SANS Cyber Defense Initiative 2017	Washington, DCUS	Dec 12, 2017 - Dec 19, 2017	Live Event
SANS Security East 2018	New Orleans, LAUS	Jan 08, 2018 - Jan 13, 2018	Live Event
SANS SEC460: Enterprise Threat Beta	San Diego, CAUS	Jan 08, 2018 - Jan 13, 2018	Live Event
SEC599: Defeat Advanced Adversaries	San Francisco, CAUS	Jan 15, 2018 - Jan 20, 2018	Live Event
SANS Amsterdam January 2018	Amsterdam, NL	Jan 15, 2018 - Jan 20, 2018	Live Event
Northern VA Winter - Reston 2018	Reston, VAUS	Jan 15, 2018 - Jan 20, 2018	Live Event
SANS Dubai 2018	Dubai, AE	Jan 27, 2018 - Feb 01, 2018	Live Event
SANS Las Vegas 2018	Las Vegas, NVUS	Jan 28, 2018 - Feb 02, 2018	Live Event
Cyber Threat Intelligence Summit & Training 2018	Bethesda, MDUS	Jan 29, 2018 - Feb 05, 2018	Live Event
SANS Miami 2018	Miami, FLUS	Jan 29, 2018 - Feb 03, 2018	Live Event
SANS London February 2018	London, GB	Feb 05, 2018 - Feb 10, 2018	Live Event
SANS Scottsdale 2018	Scottsdale, AZUS	Feb 05, 2018 - Feb 10, 2018	Live Event
SANS Secure India 2018	Bangalore, IN	Feb 12, 2018 - Feb 17, 2018	Live Event
SANS Southern California- Anaheim 2018	Anaheim, CAUS	Feb 12, 2018 - Feb 17, 2018	Live Event
SANS Dallas 2018	Dallas, TXUS	Feb 19, 2018 - Feb 24, 2018	Live Event
SANS Secure Japan 2018	Tokyo, JP	Feb 19, 2018 - Mar 03, 2018	Live Event
Cloud Security Summit & Training 2018	San Diego, CAUS	Feb 19, 2018 - Feb 26, 2018	Live Event
SANS Brussels February 2018	Brussels, BE	Feb 19, 2018 - Feb 24, 2018	Live Event
SANS London November 2017	OnlineGB	Nov 27, 2017 - Dec 02, 2017	Live Event
SANS OnDemand	Books & MP3s OnlyUS	Anytime	Self Paced